

# NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE GRIP



## KEY FEATURES

- ✓ Continuous weave configuration
- ✓ No fraying wires
- ✓ Lighter and safer to handle
- ✓ Longer Life

Ideal for fiber optic applications, offshore or for a multitude of uses in the electrical industry; dramatically improved weight to break ratio. Slingco's non-metallic pulling grips are made of a high-strength, non-metallic aramid fiber, with UV protective coating; they are suitable for pulling both single cable and cable bundles. These woven mesh grips offer a non-metallic alternative to steel. Non-metallic material is easy to work with even without gloves.

### Single Eye Single Weave Non-Metallic Grip

| Slingco Part No. | Range (mm) | Range (in)  | Lattice Length (mm) | Lattice Length (in) | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------|------------|-------------|---------------------|---------------------|-------------------------|-------------------------|
| ZCS1040          | 10 - 20    | 0.38 - 0.75 | 552                 | 21                  | 1,115                   | 2,460                   |
| ZCS1022          | 20 - 30    | 0.75 - 1.25 | 523                 | 21                  | 1,620                   | 3,580                   |
| ZCS2923          | 25 - 38    | 1.00 - 1.50 | 573                 | 23                  | 1,620                   | 3,580                   |
| ZCS1041          | 30 - 40    | 1.25 - 1.50 | 642                 | 25                  | 2,230                   | 4,920                   |
| ZCS1042          | 40 - 50    | 1.50 - 2.00 | 485                 | 19                  | 2,640                   | 5,820                   |

### Single Eye Double Weave Non-Metallic Grip

| Slingco Part No. | Range (mm) | Range (in)  | Lattice Length (mm) | Lattice Length (in) | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------|------------|-------------|---------------------|---------------------|-------------------------|-------------------------|
| ZCS1023          | 30 - 40    | 1.25 - 1.50 | 642                 | 25                  | 4,470                   | 9,860                   |
| ZCS1024          | 40 - 50    | 1.50 - 2.00 | 523                 | 21                  | 5,390                   | 11,880                  |
| ZCS1179          | 50 - 65    | 2.00 - 2.50 | 636                 | 25                  | 7,210                   | 15,900                  |
| ZCS1180          | 65 - 76    | 2.50 - 3.00 | 908                 | 36                  | 7,210                   | 15,900                  |
| ZCS1181          | 76 - 102   | 3.00 - 4.00 | 1,029               | 40                  | 7,210                   | 15,900                  |
|                  | 100 - 125  |             | 3,168               |                     | 7,210                   |                         |

### Single Eye Double Weave High Strength Non-Metallic Grip

| Slingco Part No. | Range (mm) | Range (in)  | Lattice Length (mm) | Lattice Length (in) | Approx. Break Load (kg) | Approx. Break Load (lb) |
|------------------|------------|-------------|---------------------|---------------------|-------------------------|-------------------------|
| ZCS13054         |            | 4.00 - 5.00 |                     | 118                 |                         | 45,500                  |

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

### Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.



## GET IN TOUCH



1 888 685 9478





[sales@slingcoamerica.com](mailto:sales@slingcoamerica.com)

## NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE GRIP

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.



### GET IN TOUCH

 1 888 685 9478  
 [sales@slingcoamerica.com](mailto:sales@slingcoamerica.com)