

## **REELSTRONG CLD14**

SINGLE REEL TRAILER WITH 14,000 LBS CAPACITY



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



## **REELSTRONG CLD14**

SINGLE REEL TRAILER WITH 14,000 LBS CAPACITY

## **EQUIPMENT SPECS**

**REEL CARRIER SPECIFICATIONS:** 

CAPACITY: SINGLE 108" D X 60" W X 3" CENTER HOLE X 14,000 LBS

2 7/8" REEL BAR WITH CROSSARM AND (1) LOCKING COLLAR, ROTATING IN NON ENCAPSULATED NYLATRON BEARING SADDLE

TENSIONING BRAKE ASSEMBLY:

16" BRONZE ALLOY TRU-STOP VENTILATED REEL BRAKE W/ VENTILATED GUARD

**HYDRAULIC TAKE UP/ PAY OUT ASSEMBLY:** 

DIRECT DRIVE TO REEL BAR, ELIMINATES PROBLEMS ASSOCIATED WITH RIM DRIVE SYSTEMS

3,300 FT/LBS TORQUE HYDRAULIC TAKE-UP RETRIEVER

3,700 LBS. OF LINE PULL ON A 24" DRUM @ 2,500 PSI

MOTOR SPOOLED W/ REEL BRAKE FOR SMOOTH INSTANT REEL STOPPAGE

CONTROL VALVE WITH ADJUSTABLE SPEED CONTROL FOR TAKE UP/ PAY OUT

HYDRAULIC CABLE REWIND LEVELER

**HYDRAULIC POWER PACK: 13 HP GAS ENGINE WITH ELECTRIC START** 

**APPROX 6.7 GPM AT 3,600 RPM AND 2250 PSI** 

TRAILER SPECIFICATIONS:

**GVWR: 22,100 LBS., 14,000 LBS. APPROX. PAYLOAD** 

TANDEM 10,000 LBS. TORSION AXLES

**ELECTRIC BRAKES** 

OVERALL LENGTH: 198" WIDTH: 102" HEIGHT: 84.5" WEIGHT: 5,050 LBS

BED LENGTH: 76.75" WIDTH: 66.5"

12,000 LBS. STATIC FRONT JACK WITH SPRING RETURN

(2) 8,000 LBS. JACKS ON REAR CORNERS

**FULLY ADJUSTABLE 6 POSITION 3" LUNETTE EYE** 

**12 VOLT WIRING SYSTEM** 

ICC AND DOT APPROVED LED LIGHTS

**GALVANIZED WITH TEN (10) YEAR STRUCTURAL WARRANTY** 







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com