



# LOAD KING LK-122-PT POLE TRAILER

WITH 12,500 LB. PAYLOAD



# SPECS

CAPACITY : 16,000 LB. GVWR / 12,500 LB. PAYLOAD

AXLES : 7K DUAL AXLE

TIRES : ST235/80R16 LR-E

WHEELS : 16" X 6" SINGLE WHITE MOD

LENGTH ADJUSTMENTS : 24'/31'/40'

CARGO BED : 142"L X 64"W X 15"H

OVERALL WIDTH : 92"

FRONT BOLSTER:

45" TUBULAR BOLSTER

64" TUBULAR BOLSTER

60" WIDE W/ LEVER LOCK STANCHIONS

89" WIDE W/ LEVER LOCK STANCHIONS"

CENTER/REAR BOLSTERS

64" WIDE W/ POLE STOPS

89" WIDE REMOVABLE W/ STANCHIONS

TONGUE & HITCH : 8" X 4" EXTENDABLE TONGUE W/ WEAR PADS"

HITCHPLATE : 6-POSITION ADJUSTABLE WITH 2 1/2" LUNETTE EYE

JACK : 3" LUNETTE EYE

TOOL BOX : 14" TALL X 24" DEEP X 64" WIDE

REEL STANDS:

2,000 LB. CAPACITY - MAX REEL 72" X 48"

3,500 LB. CAPACITY - MAX REEL 72" X 54"

REEL BAR : 3 7/8" OD - INCLUDED W/ REEL STANDS

RECEIVER POCKETS : ADDITIONAL TO ACCOMMODATE 2 OR 3 REELS



833-955-7732  
[www.loadkingmfg.com](http://www.loadkingmfg.com)

**LOAD KING**<sup>™</sup>  
BY CUSTOM TRUCK (1) SOURCE

\*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.