



SPECS

GENERAL SPECS:

PULLING FORCE: 22,000LBS

TANDEM AXLE CHASSIS

KOHLER DIESEL ENGINE

56 HP (MODEL KDI 1903 TCR, TIER 4 FINAL)

LENGTH OF CABLE - 3,150 FT

TYPE OF CABLE - 5/8" DIAMETER BRAIDED STEEL, "ANTI TWIST"

ELECTRONIC MEASURING SYSTEM (TM 3000 - US VERSION)

FEATURES:

DOUBLE CAPSTAN SYSTEM (BOTH CAPSTAN HEADS ARE DRIVEN)

LARGE DRUM CAPACITY FOR LONG ROPE LENGTHS

HYDROSTATIC DRIVE FOR CAPSTAN SYSTEM AND ROPE DRUM

THIS IS NOT A CHAIN DRIVEN SYSTEM

FULLY ENCLOSED METAL HOOD PROTECTS ALL COMPONENTS AND PROVIDES EASY ACCESS TO CONTROL PANEL AND INTERNAL COMPONENTS FOR MAINTENANCE AND REPAIR

WELL PRIMED WITH PULLER PAINTED INDUSTRIAL WHITE AND THE CHASSIS PAINTED BLACK

DRIVE: HYDRAULIC

ENGINE: 3 CYLINDER, 56 HP DIESEL, ELECTRIC START

PULLING FORCE: 22,000LBS

PULLING SPEED: 0-80 FT/MIN

CABLE LENGTH: 3,150 FT

CABLE DIAMETER: 5/8"

OVERALL LENGTH: 182"

WIDTH: 72"

HEIGHT: 71"

WEIGHT: 7,750 LBS

DRIVE:

HYDRAULIC PUMP IS DESIGNED TO ASSURE SMOOTH OPERATION WITHOUT JERKING OF PULL SPEED

STORAGE DRUM:

HYDRAULICALLY DRIVEN OPERATION AND BRAKING

MAX CAPACITY FOR 5/8" ROPE IS 3,800 FT

LEVEL WIND:

STEEL WIRE ROPE RUNS DIRECTLY FROM THE CAPSTAN SYSTEM TO THE STORAGE DRUM

AN AUTOMATIC LEVEL-WIND SYSTEM GUARANTEES SMOOTH WINDING OF THE CABLE

CHASSIS:

FRAME CONSISTING OF STEEL RECTANGULAR TUBE WITH A SQUARE TUBE REAR CROSS MEMBER. TANDEM AXLE WITH ELECTRIC BRAKE, 185 R 14 TIRES, DOT APPROVED LIGHTS, BREAKAWAY SYSTEM, 6-WAY TRAILER PLUG, TOOL BOX MOUNTED ON TONGUE



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

