



# REELSTRONG PL-1RT8-DO POWER WIND

SINGLE REEL TURRET TRAILER - 96 X 60 X 8,000 LBS REEL CAPACITY



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)



# REELSTRONG PL-1RT8-DO POWER WIND

SINGLE REEL TURRET TRAILER - 96 X 60 X 8,000 LBS REEL CAPACITY

## EQUIPMENT SPECS

### REEL / TURRET SPECIFICATIONS:

**CAPACITY: SINGLE REEL UP TO 96" DIA. x 60" W (ADJUSTABLE POSITIONS AT 72", 84", AND 96")**  
**APPROX. REEL PAYLOAD: 8,000 LBS (PAYLOAD REDUCED AS OPTIONS ARE ADDED)**  
**2.5" REEL BAR WITH PINLESS POWERLOCK™ REEL BAR SECUREMENT**  
**OPEN-TOP, NON-ENCAPSULATED NYLATRON BEARING SADDLES FOR LOW FRICTION AND EASY PAY-OUT**  
**INDUSTRY-LEADING 20" OVERSIZED TURRET BEARING, LOCKABLE ON 3-DEGREE INCREMENTS**

### HYDRAULIC POWER WIND AND TENSIONING / BRAKE ASSEMBLY:

**13 HP HONDA ENGINE HYDRAULIC POWER PACK, COMPLETE WITH ENGINE COVER, 15-GALLON RESERVOIR**  
**3,300 FT-LB TORQUE HYDRAULIC TAKE-UP RETRIEVER**  
**16" BRONZE ALLOY VENTILATED REEL BRAKE WITH VENTILATED GUARD**

### TRAILER SPECIFICATIONS:

**GVWR: 13,800 LBS @ 15% TONGUE WEIGHT**  
**AXLE: SINGLE 12,000 LB SPRUNG AXLE**  
**WHEELS: (2) 17.5" x 6.75" HC, 8-LUG (8 ON 6.5" BOLT CIRCLE) WITH 0.19" INSET**  
**TIRES: (2) ST-235/75R17.5 LOAD RANGE J**  
**BRAKES: 12.25" x 5.00" ELECTRIC WITH SAFETY BREAKAWAY KIT**  
**OVERALL LENGTH: 157", WIDTH: 101.75", HEIGHT: 101.75"**  
**CURB WEIGHT: APPROX. 4,100 LBS (VARIES WITH OPTIONS)**  
**HEAVY-DUTY 6" x 3" x 1/4" STRUCTURAL FRAME**  
**FULLY ADJUSTABLE 6-POSITION HITCH**  
**12,000 LB STATIC FRONT JACK WITH SPRING RETURN AND (2) 8,000 LB STATIC REAR STABILIZER JACKS**  
**1/8" FABRICATED DIAMOND-PLATE FENDERS AND WHEEL CHOCK HOLDERS**

### ELECTRICAL & SAFETY:

**12-VOLT WIRING SYSTEM WITH DOT / ICC APPROVED LED LIGHTING WITH HIGH-VISIBILITY MARKERS**  
**SEALED, RUBBER-MOUNTED STOP, TURN, TAIL, AND MARKER LIGHTS**  
**100% SEALED, HEAT-SHRINKED WIRING CONNECTIONS WITH FULL LOOM**  
**FRAME-BONDED GROUND LUG**

### FINISH:

**GALVANIZED FRAME WITH TEN (10) YEAR STRUCTURAL WARRANTY**



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

**888-925-0858**  
**www.customtruck.com**