



SHERMAN + REILLY P-6000H

HERITAGE 6000 LB. SINGLE DRUM PULLER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN + REILLY P-6000H

HERITAGE 6000 LB. SINGLE DRUM PULLER

FEATURES

- 1. SAFE-ZONE® ENCLOSURE WITH OCU-VIEW™.
- 2. ALL STRINGING OPERATIONS CONTROLLED FROM THE SAFETY OF THE SAFE-ZONE® ENCLOSURE.
- 3. CHAIN DRIVE; SINGLE HYDRAULIC MOTOR, PENTA-DRIVE COUPLING SYSTEM WITH REMOTE ENGAGEMENT.
- 4. HELICOPTER-READY PAYOUT BRAKE.
- 5. MANUAL JACKS STANDARD ON BUMPER (2) AND TONGUE
- CAPABLE OF PULLING 6,000 LB. ON A 62 IN. DIAMETER REEL.
- MAXIMUM LINE SPEED: PULLING 6 MPH.
- **DRUM CAPACITY:**
- 15,500 FT. OF 3/4 IN. PE-12
- 25,000 FT. OF 1/2 IN. ULTREX M SYNTHETIC ROPE
- 25,000 FT. OF 11MM HD (7/16") ANTI TWIST WIRE ROPE
- RATCHET PAWL FAILSAFE BRAKE

SPECIFICATIONS

- MAXIMUM PULLING CAPACITY - 6,000 LB. (RATED AT 30 IN. FROM DRUM CENTER)
- MINIMUM TENSIONING CAPACITY - 1,250 LB. AT TOP OF DRUM AND 3,500 LB. AT CORE
- MAXIMUM LINE SPEED PULLING: - 6 MPH
- TENSIONING: - 30 RPM
- MECHANICAL PAYOUT BRAKE - 27.75 IN. BRONZE DISC, HELICOPTER-READY
- RECONDUCTORING REEL SIZE - 72 IN. DIAMETER / 45 IN. WIDTH
- MAXIMUM REEL WEIGHT - DYNAMIC OVER THE ROAD 6,400 LB. - STATIC JACKS EXTENDED 11,000 LB.
- **DRUM DIMENSIONS CORE**
- DIAMETER: 24 IN.
- USABLE WIDTH: 36 IN.
- FLANGE DIAMETER: 62 IN.
- DRIVE SYSTEM CHAIN DRIVE: SINGLE HYDRAULIC MOTOR PENTA-DRIVE COUPLING SYSTEM WITH REMOTE ENGAGEMENT
- **DRIVE SYSTEM ENGINE**
- TURBOCHARGED, TIER-4 FINAL DIESEL, 116 HP, WATER-COOLED KUBOTA®
- FUEL CAPACITY - 30 GALLONS
- HYDRAULIC FLUID - ISO GRADE 32
- HYDRAULIC RESERVOIR - 25 GALLON (32 USABLE GALLONS)
- HYDRAULIC FLUID FILTRATION - 10 MICRONS, RETURN FILTER
- LEVELWIND - HYDRAULICALLY DRIVEN, OPERATOR STEADYREST™ CONTROLLED DIRECTIONAL CHANGE
- OPERATOR'S SAFETY ENCLOSURE OPEN-AIR SAFE-ZONE® ENCLOSURE
- FRAME CONSTRUCTION STEEL TUBING, STEEL PLATE, CONTINUOUS WELD
- **DIMENSIONS**
- LENGTH (OVERALL, NOM.) 20 FT. 6 IN.
- WIDTH (OVERALL, NOM.) 8 FT. 6 IN.
- HEIGHT (OVERALL, NOM.) 9 FT. 4 IN.
- WEIGHT (WITHOUT ROPE) 13,410 LB. WITHOUT ROPE 15,765 LB. WITH DRUM & ROPE
- GVWR 20,500 LB.

- **TRAILER**
- AXLE CONFIGURATION / SUSPENSION - TANDEM / LEAF-SPRING
- WHEEL CONFIGURATION & TIRES - SINGLE 235/75R 17.5 LJR
- BRAKES (TRAILER) - ELECTRIC, WITH BREAKAWAY SWITCH & VISUAL INDICATOR FOR BATTERY CHARGE STATE.
- TOWING ATTACHMENT - 3 IN. PINTLE EYE, WITH TWO SAFETY CHAINS & HOOKS
- TIE DOWNS - (4) 1 IN. DIAMETER STEEL D-RINGS
- (2) HYDRAULIC REAR BUMPER JACKS - (1) SINGLE HYDRAULIC TONGUE JACK
- TONGUE JACK - TWO SPEED DROP, PIN, AND CRANK
- BATTERY / ELECTRICAL SYSTEM - (2) 12V/810 CCA/GROUP 27
- LIGHTS / NAVIGATION - US DOT, LED, 12 VDC
- GROUNDING - (2) GRADE 5H
- WHEEL CHOCKS - STANDARD (2)
- (1) FIRE EXTINGUISHER ABC
- COLOR S+R WHITE



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



LOAD KING LK-3DPT-6K

THREE DRUM WATERFALL PULLER-TENSIONER

CAB & OPERATOR CONTROLS

- FULLY ENCLOSED CAB WITH CLIMATE CONTROL-HEAT, AIR CONDITIONING, LIGHTS AND LARGE CAPTAIN'S CHAIR
- HYDRAULIC RAISING CAB – ALLOWS THE OPERATOR TO RAISE THE CAB HEIGHT TO BETTER SEE THE DRUMS WHEN WORKING.
- OPERATOR CONTROLS – ALL CONTROLS ARE CLOSE AND ACCESSIBLE TO THE OPERATORS TOUCH.
- PRE-SETTABLE SPEED, PULLING & TENSIONING FORCE VIA 12" COLOR CODED TOUCH PAD
- TOGGLE SWITCH ACTUATED, FINE ADJUSTMENT OF PULLING OR TENSIONING SPEED & FORCE DURING OPERATION
- LIVE ACTUAL PULL OR TENSION FORCE READ OUT WITH SPEED AND DISTANCE. BOTH DIGITAL AND DIAL DISPLAY
- SELF-DIAGNOSTICS – FAULT CODES
- INDIVIDUAL TENSION / OVERSPIN BRAKE CONTROLS WITH PARKING BRAKE
- FOOT PEDAL TENSION/ OVERSPIN BRAKE OPERATION
- SINGLE STICK PAY IN – PAY OUT DRUM CONTROL INCLUDING THUMB SWITCH WITH FINE ON DEMAND PULL & TENSION CONTROL
- SINGLE STICK ARMREST MOUNTED EVENWIND CONTROL WITH THUMB SWITCH SPEED CONTROL WITH SCREEN DISPLAY
- LED LIGHTING THAT CONFIRMS TO THE OPERATOR THAT A DRUM IS ENGAGED OR DISENGAGED
- ENGINE MONITOR SCREEN WITH ADJUSTABLE THROTTLE SPEED
- 12V POSITIVE & NEGATIVE THREADED STUDS FOR COMMUNICATIONS RADIO INSTALLATION. WALL MOUNTED RADIO HOLDER.
- FOLD UP LADDER AND WIDE EXPANDED METAL OPERATOR ACCESS STEPS TO CAB
- EXPANDED METAL FRONT CAB SCREEN TO PROTECT OPERATOR

CUSTOM TRAILER MOUNT

- CUSTOM SHORT HD DESIGNED 5TH WHEEL, THREE AXLE STEP DECK TRAILER. FIXED TANDEM WITH SPRING SUSPENSION AND 3RD REAR AIR LIFT AXLE. 60,000 LB. GVWR, SUPER SINGLE RADIAL TIRES, 42" BOTTOM DECK HEIGHT. HD. HYDRAULIC FRONT JACKS
- MANUAL HAND CRANK FRONT LANDING GEAR. HD EXTENDED REAR PUSH BUMPER.

ENGINE & HYDRAULIC CAPACITY

- • ENGINE - 173 HP JCB TIER IV FINAL WATER-COOLED DIESEL ENGINE
- • FUEL TANK - 30 GALLONS
- • HYDRAULIC TANK - 30 GALLONS

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com