



REELSTRONG CPTL20

16,400 LBS CAPACITY TANDEM AXLE CARGO POLE TRAILER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



REELSTRONG CPTL20

16,400 LBS CAPACITY TANDEM AXLE CARGO POLE TRAILER

EQUIPMENT SPECS

POLE TRAILER SPECIFICATIONS:

CAPACITY: CPTL20 – 22,100 LBS. GVWR @ 15% TONGUE WEIGHT, 16,400 LBS. APPROX. POLE PAYLOAD
LIFETIME WARRANTY MEGA-ROLLER™ 6-ROLLER TELESCOPING TONGUE (NO WEAR PADS TO MAINTAIN OR REPLACE)
SELF-SECURING SECURELOCK™ TONGUE-LOCK (NO LOOSE PIN)
NON-BINDING / NON-FREEZING EZ SLIDE POLE CENTERING STANCHIONS
ALL POLE RESTS: 5" H-BEAM POLE SEATS
WINCH BINDERS W/ RATCHETING BREAKER BAR

TRAILER SPECIFICATIONS:

AXLES: TANDEM 10,000 LBS. SPRUNG
(4) 17.50 X 6.75 HC / 8 ON 6.5 BC W/ 0.19 INSET WITH (4) ST-215/75R17 LR-H TIRES
ELECTRIC BRAKES – 12.25" X 3.38" WITH SAFETY BREAKAWAY KIT WITH ABSORBED GLASS MAT (AGM) BATTERY
OVERALL LENGTH (RETRACTED / EXTENDED): 25' / 29' / 33' / 37'
OVERALL WIDTH: 89.00", CURB WEIGHT: 5,650 LBS. APPROX., POLE SEAT HEIGHT: 45"
CARGO BED: BED LENGTH 113.75", WIDTH 63.75", HEIGHT 15"

STANDARD TRAILER BODY:

6" X 6" X 3/8" MALE EXTENDABLE TONGUE ("SQUARE" FOR MAX EQUAL LATERAL AND VERTICAL STRENGTH)
8" X 8" X 1/4" WALL FEMALE TONGUE TUBE WITH 6" X 3" X 1/4" WALL FRAME
7-POSITION ADJUSTABLE HITCH WITH 1/2" X 42" GR70 YELLOW ZINC SAFETY CHAINS
12,000 LBS. STATIC FRONT JACK W/ SPRING RETURN
FRONT REMOVABLE / ADJUSTABLE POLE SEAT MOUNTED ON FRONT MALE TONGUE
60" WIDE 5" H-BEAM POLE SEAT W/ EZ-SLIDE STANCHIONS AND SIX (6) D-RINGS FRONT, CENTER AND REAR FOR CARGO
REMOVABLE LIGHT BAR WITH FLAG HOLDERS AND FLAGS, 35' POWER CABLE WITH 7-WAY PLUG

WIRING:

DOT / ICC — FMVSS / CMVSS APPROVED LED ULTRA-HIGH VISIBILITY 180 DEGREE BULLET MARKER AND CLEARANCE LIGHTS
LED SEALED BEAM, RUBBER MOUNTED STOP, TURN, TAIL AND MARKER LIGHTS
100% SEALED HEAT-SHRUNKED WIRING CONNECTIONS W/ FULL LOOM
FULLY PROTECTED 6 WAY FEMALE PLUG ACTS AS JUNCTION BOX RECESSED IN FRAME RAIL (NO PLASTIC JUNCTION BOXES)

FINISH:

GALVANIZED WITH TEN (10) YEAR STRUCTURAL WARRANTY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com