



# PL-3RT8 SAFELOCK TRIPLE REEL, TURRET BASE POWER WIND REEL TRAILER



# SPECS

38,500 LBS. GVWR @ 15% TONGUE WEIGHT  
24,000 LBS. APPROX. (8,000 LBS. PER TURRET)  
TANDEM AXLE-DUAL 22.5K LBS. SPRUNG  
(8) 17.5 X 6.75 HC / 8 ON 10.8 BC W/ 5.60 OUTSET  
(8) ST-235/75R17.5 16PR TIRES  
12.25" X 5.00" ELECTRIC W/ SAFETY BREAKAWAY KIT

#### TRAILER DIMENSIONS:

- 367" LONG APPROX.
- 100" WIDE APPROX.

#### STANDARD TRAILER BODY:

HEAVY DUTY 10" X 4" X 1/4" FRAME  
6-POSITION ADJUSTABLE HITCH  
1/2" X 36" GR70 YELLOW ZINC SAFETY CHAINS WITH HOOKS  
12,000 LBS. STATIC FRONT JACK W/ SPRING RETURN  
GROUND LUG: COPPER ALLOY BOLTED TO FRAME  
FENDERS: 1/8" TREAD PLATE

#### STEPS:

GRIP STRUT  
(4) 12,000 LBS. STATIC STABILIZER JACKS W/ SPRING RETURN

#### WIRING:

DOT / ICC APPROVED LED LIGHTS AND CONSPICUITY REFLECTIVE TAPE  
FMVSS / CMVSS STANDARD 108 LED LIGHTING  
SEALED BEAM, RUBBER MOUNTED STOP, TURN, TAIL AND MARKER LIGHTS

#### TURRET BASE, REEL STANDS, BRAKES, POWER WIND:

84" DIAMETER X 60" WIDE X 8000 LB. X 2.5" ARBOR WITH CENTERING COLLARS  
OVERSIZED 20" TURRET BEARINGS - 250K AXIAL, 90K FT/LBS MOMENT LOAD LOCKABLE ON 6 DEG. INTERVALS.  
VIRTUALLY EFFORTLESS TO ROTATE MANUALLY LOADED OR UNLOADED.  
THREE POINT CONTACT STEPS AND REMOVABLE CHAINED GRAB HANDLES ON FRONT AND REAR - STANDARD.  
TEN INCH REINFORCED RECTANGULAR TUBE FRAME RAILS.  
16" BRONZE VENTILATED SELF-COOLING TRU-STOP TENSION BRAKE.  
3,300 FT LB. POWER WINDER/RETRIEVER. INDUSTRY'S STRONGEST FOR PULLING OUT OLD LINES AND PAY IN/PAY-OUT.  
CAPSTAN/COLLAPSIBLE REEL ADAPTER

#### 35 HP VANGUARD POWER PACKAGE INCLUDES:

HYDRAULIC OIL COOLER (REQUIRED FOR FLOW CONTROLLED SYSTEM. COMPARE  
W/ COMPETITION THAT DOES NOT PROVIDE)  
CENTRAL VALVE BANK ON FENDER W/ 3 X DETENTED BUCHER BRAND SINGLE VALVES (PLUMBED POWER BEYOND)  
8 GPM FINE METERING FLOW CONTROLS (ONE PER VALVE)  
"PREMIUM" TRIPLE PORT PUMP (NON-STACKED, OFF THE-SHELF RESERVOIR. NOT CUSTOM)  
ALL COMPONENTS PREMIUM AND OFF SHELF  
HYDRAULIC HOSE SWIVEL TO 100% PREVENT HYDRAULIC HOSE PINCHING AND MAINTENANCE.  
GALVANIZED W/ TEN (10) YEAR WARRANTY



888-925-0858

[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

