



LOAD KING LK112PT

19,500 LB CAPACITY TANDEM AXLE POLE TRAILER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



LOAD KING LK112PT

19,500 LB CAPACITY TANDEM AXLE POLE TRAILER

EQUIPMENT SPECS

POLE TRAILER SPECIFICATIONS:

CAPACITY: 24,700 LB. GVWR, 19,500 LB. PAYLOAD CAPACITY

26'9" / 33'7" / 40'5" OVERALL LENGTH ADJUSTMENTS

95" OVERALL WIDTH, 42" BOLSTER HEIGHT, APPROX. 5,200 LB. WEIGHT

CARGO BED: 124" L X 41" W X 7" H

95" WIDE FRONT ADJUSTABLE TUBULAR BOLSTER WITH 95" WIDE CENTER/REAR RECTANGULAR TUBE BOLSTERS

21" LEVER-LOCK STANCHIONS WITH FRONT SINGLE-POLE CRADLE

(3) HEAVY-DUTY RATCHET WINCH BINDERS WITH BREAKER BAR AND 27' X 4" NYLON STRAPS

TRAILER SPECIFICATIONS:

TANDEM 12,000 LB. AXLES WITH SLIPPER SPRING SUSPENSION

OIL BATH HUBS, ELECTRIC BRAKES AND ADJUSTABLE SPRING PADS FOR AXLE ALIGNMENT

REINFORCED SPRING HANGERS WITH 3" STRUCTURAL CHANNEL

(8) 235/80R16 E TIRES IN DUAL CONFIGURATION WITH RUBBER WHEEL CHOCKS

STANDARD TRAILER BODY:

8" X 4" X 1/4" WALL EXTENDABLE TONGUE WITH EXTENSION-ASSIST ROLLER AND UHMW-PE WEAR PADS

BOLT-ON COLLAR WITH SEALED BEARING ROLLER FOR EASY EXTENDING AND RETRACTING

5-POSITION ADJUSTABLE HITCH PLATE WITH 2.5" LUNETTE EYE, 42,000 LB. CAPACITY

3/8" X 36" SAFETY CHAINS WITH SAFETY HOOKS

5" OFFSET TUBULAR A-FRAME SUPPORTS WITH 12,000 LB. STATIC LOAD DROP-LEG JACK

7" X 3" TUBULAR STEEL FRAME WITH 10" X 6" RECEIVER TUBE

12 GA CARGO FLOOR WITH DRAINAGE PERFORATIONS AND (4) D-RINGS

WIRING:

ICC & DOT APPROVED LED LIGHTS

SEALED BEAM RUBBER-MOUNTED STOP, TURN, TAIL AND MARKER LIGHTS

32" PIGTAIL WITH 7-WAY RV PLUG

BREAKAWAY KIT WITH SEALED LEAD ACID BATTERY

FINISH:

SANDBLASTED, SEALED, EPOXY PRIMED AND FINISHED WITH POLYURETHANE TOPCOATS

ATTACHMENTS PAINTED BEFORE ASSEMBLY AND INSTALLED WITH SERVICEABLE FASTENERS



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com