



REELSTRONG PT30-RE

25,000 LBS CAPACITY TANDEM AXLE POLE TRAILER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



REELSTRONG PT30-RE

25,000 LBS CAPACITY TANDEM AXLE POLE TRAILER

EQUIPMENT SPECS

POLE TRAILER SPECIFICATIONS:

CAPACITY: PT30-RE – 34,500 LBS. GVWR @ 15% TONGUE WEIGHT, 25,500 LBS. APPROX. POLE PAYLOAD
LIFETIME WARRANTY MEGA-ROLLER™ 6-ROLLER TELESOPING TONGUE W/ BRONZE BEARINGS AND 8-ROLLER TELESOPING
REAR EXTENSION W/ BRONZE BEARINGS (NO WEAR PADS TO REPLACE)
SELF-SECURING SECURELOCK™ TONGUE-LOCK (NO LOOSE PIN)
NON-BINDING / NON-FREEZING EZ-SLIDE POLE CENTERING STANCHIONS
5" H-BEAM POLE SEATS W/ WINCH BINDERS AND BREAKER BAR

TRAILER SPECIFICATIONS:

AXLES: TANDEM 15,000 LBS. SPRUNG
(8) 17.5 X 6.75 HC / 8 ON 275MM BC W/ 5.60 OUTSET WITH (8) ST-215/75R17.5 LR-H TIRES
ELECTRIC BRAKES – 12.25" X 5.00" W/ SAFETY BREAKAWAY KIT
OVERALL LENGTH (RETRACTED / EXTENDED): 34.25' / 40.5' / 46.75' / 53' / 63'
CURB WEIGHT: 8,700 LBS. APPROX.
MATERIAL BED: 100" X 41"

STANDARD TRAILER BODY:

6" X 6" X 3/8" WALL MALE EXTENDABLE TONGUE ("SQUARE" FOR MAX EQUAL LATERAL AND VERTICAL STRENGTH)
8" X 8" X 1/4" WALL FEMALE TONGUE TUBE
REAR EXTENSION TUBES: 7" X 3" X 1/4" MALE / 8" X 4" X 1/4" FEMALE
7-POSITION ADJUSTABLE HITCH WITH 1/2" X 42" ZINC PLATED GR70 SAFETY CHAINS
12,000 LBS. STATIC FRONT JACK W/ SPRING RETURN
1/8" FABRICATED DIAMOND PLATE FENDERS AND WHEEL CHOCK HOLDERS

WIRING:

DOT / ICC – FMVSS / CMVSS APPROVED LED ULTRA-HIGH VISIBILITY 180 DEGREE BULLET MARKER AND CLEARANCE LIGHTS
LED SEALED BEAM, RUBBER MOUNTED STOP, TURN, TAIL AND MARKER LIGHTS
INTERNAL CAT TRACK PROTECTS WIRING
100% SEALED HEAT-SHRINKED WIRING CONNECTIONS W/ FULL LOOM
FULLY PROTECTED 7 OR 6 WAY FEMALE PLUG ACTS AS JUNCTION BOX RECESSED IN FRAME RAIL (NO PLASTIC JUNCTION BOXES)

FINISH:

GALVANIZED WITH TEN (10) YEAR STRUCTURAL WARRANTY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com