

TEREX HI-RANGER HRX55 BUCKET TRUCK

55' OVERCENTER MATERIAL HANDLING AERIAL DEVICE



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



TEREX HI-RANGER HRX55 BUCKET TRUCK

55' OVERCENTER MATERIAL HANDLING AERIAL DEVICE

EQUIPMENT SPECS

WORKING HEIGHT: 60.3'

CONTINUOUS ROTATION

SIDE REACH: 42.9' (NON-OVERCENTER) / 48.3' (OVERCENTER)

AVAILABLE ON MANY DIFFERENT CHASSIS MAKES. MODELS

HYDRAULIC ARTICULATING & EXTENDING UNDER-LOAD JIB/WINCH

OPTIONAL PLATFORM LIFTER PROVIDES

24" OF VERTICAL PLATFORM LIFT

CONTROL-PLUS SINGLE-STICK CONTROLLER AT PLATFORM

700 LBS. PLATFORM CAPACITY

EXTRA HEAVY DUTY X-FRAME OUTRIGGERS W/ INTERLOCK

SIDE MOUNT 24" X 48" X 42" PLATFORM

INSULATED LINER. EXTERNAL ACCESS STEP

HYDRAULIC PLATFORM ROTATOR OFFERS

105 DEGREES OF FORWARD ROTATION

SELF-ALIGNING SWIVEL BUSHING

HYDRAULIC OVERLOAD PROTECTIONS ON ALL FUNCTIONS

BOOM STORAGE WARNING LIGHT

SUBFRAME CONSTRUCTED W/ OPEN CENTER, DUAL HYDRAULIC OUTLETS AT PLATFORM

AUXILIARY POWER SYSTEM

CUSTOMIZED LOAD CHARTS

UPPER & LOWER BOOMS: FILAMENT WOUND TAPERED FIBERGLASS CLEAR SPAN INSULATION GAP

35 GALLON HYDRAULIC OIL RESERVOIR

ENGINE THROTTLE CONTROL

ENGINE START/STOP CONTROLLED AT PLATFORM & LOWER CONTROLS







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com