



TEREX HI-RANGER TM125 BUCKET TRUCK

125' NON-OVERCENTER MATERIAL HANDLING AERIAL DEVICE



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



**CUSTOM
TRUCK**
ONE SOURCE™

TEREX HI-RANGER TM125 BUCKET TRUCK

125' NON-OVERCENTER MATERIAL HANDLING AERIAL DEVICE

EQUIPMENT SPECS

125' WORKING HEIGHT
52' SIDE REACH
CONTINUOUS UNRESTRICTED ROTATION
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS
BOTH ARTICULATING BOOM & HYDRAULIC EXTENSIONS OF UPPER & LOWER BOOM
90 DEGREES OF LOWER BOOM ARTICULATION
168 DEGREES OF UPPER BOOM ARTICULATION
HI-STRENGTH STEEL BOOM CONSTRUCTION
LOWER BOOM INSULATION GAP: 20"
UPPER BOOM: 14' CLEAR INSULATION
CONTROL-PLUS 4-FUNCTION SINGLE STICK CONTROL
HYDRAULIC/ELECTRIC PLATFORM LEVELING SYSTEM
35" X 57" X 42" FIBERGLASS PLATFORM ROTATING D-SHAPED-STYLE W/
GROUND ACCESS, 180 DEGREE HYDRAULIC ROTATOR, 800 LBS. PLATFORM CAPACITY
UPPER/LOWER CONTROL SELECTOR PROVIDES OVERRIDE OF PLATFORM CONTROLS
2,100 LBS. LIFT CAPACITY IN ALL POSITIONS W/ OUTRIGGER BOOM INTERLOCK
PILOT-OPERATED HYDRAULIC SYSTEM FOR BOOM FUNCTIONS
FULL PRESSURE HYDRAULIC SYSTEM, 3000 PSI CLOSED CENTER W/ LOAD SENSING CAPABILITIES



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com