



SPECS

HORIZONTAL REACH	22 FT. 7 IN. (6.88M)
STANDARD PLATFORM CAPACITY	300 LBS. (136KG)
OUTER BOOM TRAVEL	-8° TO +80°
INNER BOOM EXTENSION	116 IN. (2.95M)
HEIGHT TO BOTTOM OF PLATFORM	29 FT. 10 IN. (9.09M)
WORKING HEIGHT	34 FT. 10 IN. (10.6M)
STOWED TRAVEL HEIGHT	9'-9" (2.97M)
WEIGHT OF LIFT W/ MOUNTING HARDWARE	1530 LBS. (694 KG)
OPERATING PRESSURE	2250 PSI (158 KG/CM)
FLOW RATE	2 GPM (8 LPM)
FILTRATION	10 MICRON RETURN/ 100 MESH SUCTION
SYSTEM TYPE	OPEN CENTER
OPTIONS	EMERGENCY LOWERING BACK UP PUMP PNEUMATIC CIRCUIT(S) TO THE PLATFORM VARIOUS PLATFORMS, DOORS AND COVERS BUMPER EXTENSIONS 120 VOLT RECEPTACLE AT PLATFORM MANUAL PLATFORM POSITIONER BRIDGEMOUNT ELECTRIC DRIVE



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

