

VERSALIFT VST-9000-E100 TRACKED BUCKET 104' ARTICULATING TELESCOPIC ELEVATOR AERIAL DEVICE

ON CTRAC8000 CRAWLER CARRIER



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



VERSALIFT VST-9000-E100 TRACKED BUCKET

104' ARTICULATING TELESCOPIC ELEVATOR AERIAL DEVICE ON CTRAC8000 CRAWLER CARRIER

EQUIPMENT SPECS

TELESCOPIC & ARTICULATING BOOM

10' LIFT ELEVATOR

105' WORKING HEIGHT

56' 8" HORIZONTAL REACH

CONTINUOUS ROTATION

EASY REMOVAL JIB W/ 1,000 LBS. CAPACITY IN ANY POSITION

LOWER BOOM LIFT EYE CAPACITY (OPTIONAL): 1,500 LBS.

2-MAN PLATFORM W/ HYDRAULIC ROTATOR IN ALL POSITIONS

800 LBS. PLATFORM CAPACITY (700 LBS. W/ OPTIONAL JIB)

FULL PRESSURE CONTROLS AT PLATFORM

ENGINE START / STOP AT PLATFORM W/ GROUND ACCESS

SINGLE STICK CONTROLS

EASY-STOW SIDE MOUNTED

TELESCOPIC UPPER BOOM

CHASSIS INSULATION SYSTEM

OPEN CENTER HYDRAULIC SYSTEM

POWER SOURCE: PTO PUMP

OPERATING PRESSURE: 3,000 PSI

OUTER/INNER BOOM TRAVEL +/-2: -25 TO +75 DEGREES

LOWER BOOM TRAVEL +/-2: 0 TO +88 DEGREES

INNER BOOM EXTENSION: 198"

UPPER BOOM INSULATION GAP: 108"
LOWER BOOM INSULATION GAP: 24"







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



VERSALIFT VST-9000-E100 TRACKED BUCKET

104' ARTICULATING TELESCOPIC ELEVATOR AERIAL DEVICE ON CTRAC8000 CRAWLER CARRIER

CHASSIS/CARRIER SPECS

CTRAC8000:

VERSATILE, HIGH PAYLOAD, LOW GROUND PRESSURE TRACK VEHICLE
SPECIALLY DESIGNED TO DELIVER TODAY'S GENERATION OF HIGH CAPACITY CRANES & LONG-REACHING PLATFORMS TO THOSE
JOBSITES YOU CAN'T REACH ON RUBBER TIRES.

ITS UNIVERSAL CHASSIS DESIGN MAKES FOR EASY MOUNTING AND DISMOUNTING BETWEEN EQUIPMENT.

THE CRANE OR LIFT MOUNTED TO THE CTRAC8000 WILL SEE NO CHANGE IN THE STANDARD LIFT CAPACITIES, CHARTS OR RANGE DIAGRAMS.

THERE ARE NO MODIFICATIONS TO THE OUTRIGGERS OR CRITICAL COMPONENTS, MAINTAINING THE MANUFACTURER'S WARRANTY.

STANDARD TIER 4 CUMMINS ENGINE IS COMPLIANT WITH ALL US EMISSIONS STANDARDS.

EXPORT ENGINES AVAILABLE.

DUAL BOGIE WHEELS MAXIMIZE STABILITY, MAINTAIN EVEN GROUND PRESSURE & IMPROVE LATERAL STABILITY. ACCEPTS ANY CRANE/AERIAL DEVICE/TRUCK-MOUNTED EQUIPMENT REQUIRING AN 80K GVWR CHASSIS.







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.