



TEREX GENERAL 80 DIGGER DERRICK

WITH 80.3' SHEAVE HEIGHT



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



TEREX GENERAL 80 DIGGER DERRICK

WITH 80.3' SHEAVE HEIGHT

EQUIPMENT SPECS

80.3' SHEAVE HEIGHT

26,600-LB. LIFT CAPACITY @ 10' - FULLY RETRACTED

1,850-LB. LIFT CAPACITY @ 0 DEGREES - FULLY EXTENDED

36.4' DIGGING REACH

DESIGNED WITH FEWER HOSES AND A SMALLER
COLLECTOR BLOCK FOR IMPROVED MAINTENANCE
AND ACCESSIBILITY

UTILIZES THE SAME HYDRAULIC CONTROLS AND SAME
FULL-PRESSURE, OPEN-CENTERED HYDRAULIC SYSTEM
AS OTHER MODELS IN THE PRODUCT LINE

BOOM EXTENSION ROLLERS PROVIDE OPTIMAL
SUPPORT AREA AROUND THE BOOM

DIGGER HANGER SHAFT KEEPS UNSTOWED AUGER
CENTERED BELOW THE BOOM FOR EVEN LOADING
HYDRAULIC TILT POLE GUIDE INTERLOCKS TO PROTECT
THE TILT POLE GUIDE AND BOOM FROM ACCIDENTAL
DAMAGE, AND ITS DUAL HYDRAULIC CYLINDER
TRAPEZOIDAL DESIGN STABILIZES THE BOOM DURING
DIGGING AND ROTATIONAL OPERATION

STANDARD FEATURES INCLUDE A LOAD MOMENT
LIMITER, 100 DEGREES OF BOOM TRAVEL (+80 TO -20 DEGREES), DUAL
LIFT CYLINDERS, CONTINUOUS UNRESTRICTED ROTATION
AND A CUSTOM ZONED LOAD CHART

AVAILABLE WITH INSULATED, RETRACTABLE,
FIBERGLASS 4TH SECTION THAT ALLOWS CREWS TO SET POLES AND
PERFORM LINE WORK

VARIOUS HYDRAULIC DIGGERS AND AUGERS AVAILABLE
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com