



SKYLIFT PATRIOT 50 LOW PRO BACKYARD MACHINE

WITH 51' SHEAVE HEIGHT



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SKYLIFT PATRIOT 50 LOW PRO BACKYARD MACHINE

WITH 51' SHEAVE HEIGHT

EQUIPMENT SPECS

CARRIER: MOROOKA 600 VD - ROPS CERTIFIED CABINS
SPEED: 7.5 MPH
GROUND PRESSURE (OPEN CAB): 5.6 PSI
GROUND PRESSURE (CLOSED CAB): 5.8 PSI
WEIGHT: 18,600 LBS.
OPERATOR PLATFORM: UPPER RIDING COMMAND CONSOLE
LENGTH: 21' 6" L
HEIGHT: 9' 1" OVERALL
WIDTH: 77"
TRACKS: RUBBER
TILT ALARM: DIGITAL AND AUDIBLE FRONT TO BACK / SIDE TO SIDE
ENGINE: 76 HP KUBOTA TURBO
FUEL CAPACITY: 10 GALLON
HYDRAULIC OIL CAPACITY: 25 GALLON
PUMP: 15 GPM GEAR PUMP
OPERATING PSI: 3,000 PSI
CONTROLS: FULL PRESSURE UPPER
WINCH: 6,000 LBS.
AUGER DRIVE: 2 SPEED 5,800/10,500 FT. LBS. OF TORQUE
AUGER STORAGE: AUTOMATIC ON MAIN BOOM
AUGER: 18" BULLET TOOTH
ROTATION: CONTINUOUS
WORK ZONE: UNLIMITED
PAD MOUNT TRANSFORMER DECK: INTEGRATED / 3,000 LBS.
OUTRIGGER SPREAD: FRONT 8'1" REAR 14'7" FRONT TO REAR 15'5"
SHEAVE HEIGHT: 51'
WORKING HEIGHT: 55'
SIDE REACH: 45'
DIGGING RADIUS: 30'
BOOM ASSEMBLY: 3 SECTION INSULATED ALL HYDRAULIC EXTENSION
LIFT CYLINDER: 6" BORE LIFT CYLINDER
LIFTING CAPACITY: 6,000 LBS.
BOOM ANGLES: -5 DEGREES / +75 DEGREES
INSULATION: 46KV CATEGORY C PER ANSI 92.2
OUTRIGGERS: A-FRAME FRONT / RADIAL REAR



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com