

NATIONAL CRANE 9103A 26-TON BOOM TRUCK

TO 103'



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



NATIONAL CRANE 9103A 26-TON BOOM TRUCK

TO 103

EQUIPMENT SPECS

103' 4-SECTION BOOM, REAR MOUNT INSTALLATION

DUAL CONTROL STATIONS

DUAL ENGINE THROTTLE ENGINE START / STOP

LOAD MOMENT SYSTEM W/ INTERNAL WIRE A2B

BURST OF SPEED WINCH

BARE DRUM PULL - 10,200 LBS.

375 DEGREE NON-CONTINUOUS ROTATION

STRONGER, FULL LENGTH TORSION BOX

A-FRAME MAIN OUTRIGGERS

OUTRIGGER MONITORING SYSTEM

SINGLE REAR STABILIZER

340' 9/16" ROTATION RESISTANT WIRE ROPE

SINGLE LINE PULL 7,700 LBS.

OPEN CENTER HYDRAULICS

66 GAL. HYDRAULIC RESERVOIR

7 TON HEADACHE BALL

SPEEDY-REEVE BOOM TIP & SHEAVE BLOCKS

PBR-R BOOM REST

(-9 TO +80 DEGREE) BOOM ELEVATION

EASY GLIDE BOOM WEAR PADS

CONTROL KNOB ON SWING MOTOR BRAKE RELEASE

VALVE-ADJUSTS TO SWING SPEED PREFERENCE

BEARINGS ON BOOM & RETRACT CABLES-GREASED THROUGH ACCESS HOLES IN SIDE PLATES

COMPONENTS PAINTED PRIOR TO ASSEMBLY

EASY-TO-REMOVE WINCH







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.