



SHERMAN+REILLY BWT-1363

BULLWHEEL TENSIONER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN+REILLY BWT-1363

BULLWHEEL TENSIONER

EQUIPMENT SPECS

INTEGRATED REEL CARRIER
5-GROOVE BULLWHEELS WITH PRECISION SOLD-CAST URETHANE LININGS
FULLY ADJUSTABLE & ARTICULATED DISC CALIPER BRAKING OF BULLWHEELS
QUICK RELEASE OF BULLWHEEL BRAKE SYSTEMS FOR EASY REEL CHANGE

TENSIONING CAPACITY, MAX: 3,000 LB
LINE SPEED, MAX: 4 MPH
BULLWHEEL SIZE: 36 IN. DIA.
BULLWHEEL GROOVE COUNT: 5 PER BULLWHEEL
GROOVE RADIUS: 3/4 IN.
GROOVE LINING MATERIAL: POLYURETHANE, 3/4 IN. THICKNESS
TENSIONING BRAKE: 20 IN. DIA. DISC, BRONZE
BRAKE CONTROL: 3-AXIS CALIPER, MANUAL
MAX REEL SIZE: 84 IN. OD X 52 IN. WIDE
MAX REEL WEIGHT: 8,000 LB., FULLY LOADED
REEL SHIFT DIAMETER: 2-5/8 IN.
REEL BRAKE: 16 INCH. DIA DISC, BRONZE
OPERATOR'S SAFETY SCREEN & SEAT: STANDARD
LENGTH, OVERALL, NOM: 19 FT.
WIDTH, OVERALL, NOM: 8 FT., 6 IN.
HEIGHT, OVERALL, NOM: 9 FT.
SUSPENSION: LEAF SPRING
AXLE CONFIGURATION: SINGLE
BRAKES, TRAILER: ELECTRIC, WITH SAFETY BREAK-AWAY SWITCH



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com