



SHERMAN+REILLY BWT-1545

BULLWHEEL TENSIONER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN+REILLY BWT-1545

BULLWHEEL TENSIONER

EQUIPMENT SPECS

TENSIONING CAPACITY, MAX.: 5,000 LBS.
BULLWHEEL DIAMETER: 54 IN. DIA.
BULLWHEEL BRAKES: 36 IN. ALUMINUM-BRONZE (HYDRAULIC CONTROL)
NUMBER OF GROOVES: 5 - CAST SOLID URETHANE
GROOVE DIAMETER: 2 IN. PRECISION MACHINED
BULLWHEEL LINING: URETHANE CAST
BULLWHEEL TYPE: PRECISION MACHINED
FAIRLEAD ROLLERS: ADJUSTABLE URETHANE
REEL CARRIER: 96 IN. X 54 IN., 12,000 LB.
REEL SUPPORTS: SEALED BALL BEARING, QUICK RELEASE
PAYOUT BRAKE: 16 IN. ALUMINUM-BRONZE (HYDRAULIC CONTROL)
TRAILER BRAKES: ELECTRICAL (AIR W/ABS OPTIONAL)

DIMENSIONS:

LENGTH (APPROX.): 23 FT.
WIDTH (APPROX.): 8 FT.
HEIGHT (APPROX.): 9 FT. 10 IN. LOADED WITH 96 IN. REELS
WEIGHT (APPROX.): 12,850 LBS. (NOT LOADED)
AXLES: (2) 12,000 LB.
WHEELS: (4) 17.5x6.75 HC
TIRES: (4) 245-70R-17.5-L



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com