

# **HOGG & DAVIS OLT 72B BULLWHEEL TENSIONER**

OVERHEAD LINE TENSIONER



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



## **HOGG & DAVIS OLT 72B BULLWHEEL TENSIONER**

OVERHEAD LINE TENSIONER

#### **EQUIPMENT SPECS**

**DESCRIPTION:** 

OLT 72 IS DESIGNED TO INSTALL SINGLE
CONDUCTOR. CANTED BULLWHEELS PREVENT
UNNECESSARY
TWISTING OF THE CONDUCTOR DURING
INSTALLATION. REPLACEABLE DIAMETER
MOLDED SEGMENTS.
MOLDING OF THE SEGMENTS IN THIS MANOR
ELIMINATES THE GAPS BETWEEN SEGMENTS
AND CREATES A SMOOTH CABLE SURFACE. 36"
STAINLESS STEEL DISC BRAKES, WITH CENTRALIZED BRAKING
CONTROLS. ADJUSTABLE FAIRLEADS FOR MULTIPLE
SETUPS. FRONT TO BACK, LEFT TO RIGHT TO
TOWER, AND RIGHT TO LEFT TO TOWER.

#### **TENSIONING DEVICE:**

\*(2) 72" DIAMETER BULLWHEELS (WITH LINING), 8
REPLACEABLE URETHANE MOLDED LININGS PER
BULLWHEEL. (5) 2.5" GROOVES PER BULLWHEEL, 10,000 LB.
TENSIONING CAPACITY
\*TWO 36" DIAMETER STAINLESS STEEL DISCS PER BULLWHEEL
WITH HYDRAULIC CALIPERS. CHARGE
PUMP ACTUATOR WITH ROTARY ADJUSTMENT.
\*CENTRALIZED FULLY HYDRAULIC OPERATOR STATION WITH
PROTECTIVE SCREEN AND ADJUSTABLE SEAT.
\*FRONT & REAR LARGE RUBBER ADJUSTABLE FAIRLEADS.

### TRAILER:

TANDEM 7,000 LB. LEAF SPRUNG AXLES, SINGLE 235/75R17.5 TIRES, 8 BOLT RIMS, ELECTRIC TRAILER BRAKES, 7 WIRE ROUND TRAILER PLUG, ADJUSTABLE PINTLE HITCH, MANUAL TONGUE JACK, TWO REAR MANUAL JACKS, FULL COVER FENDERS. 15,000

DIMENSIONS: 17' 6" LONG 8' WIDE 10' 4" TALL (WITH FAIRLEADS OFF) 12' TALL (WITH FAIRLEADS ON) 11,000 LBS.







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.