

HOGG & DAVIS ODP 20-4 4-DRUM PULLER

WITH 2,000 LB. FULL DRUM CONTINUOUS LINE-PULL



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



HOGG & DAVIS ODP 20-4 4-DRUM PULLER

WITH 2.000 LB. FULL DRUM CONTINUOUS LINE-PULL

EQUIPMENT SPECS

PERFORMANCE:

2,000 LB. FULL DRUM CONTINUOUS LINEPULL INFINITY VARIABLE LINEPULL SPEED - 0-4 MPH

DRIVE SYSTEM:
36.8 HP YANMAR ENGINE
CLOSED LOOP HYDROSTATIC HYDRAULIC DRIVE
SPRING APPLIED, HYDRAULIC RELEASE BRAKE
MECHANICAL CLUTCH ENGAGEMENT, EACH DRUM
FREEWHEEL DISCONNECT, EACH DRUM

24" DIA. HYDRAULIC OVERSPIN BRAKE, EACH DRUM

TRAILER DATA:
SINGLE 10,000 LB. LEAF-SPRUNG AXLE
11,000 LB. GVWR
ELECTRIC TRAILER BRAKES
(3) DROP-LEG MANUAL LEVELING JACKS
(2) R17.5 - 16 PLY RATED TIRES

GENERAL FEATURES:

19 GALLON FUEL CAPACITY

29.5 GALLON HYDRAULIC OIL CAPACITY
LEVELWIND
LOCKABLE STEEL BATTERY BOX
BAKED WHITE ENAMEL FINISH









HOGG & DAVIS ODP 20-4 4-DRUM PULLER

WITH 2.000 LB. FULL DRUM CONTINUOUS LINE-PULL

OPERATOR'S CONSOLE:
PERMANENTLY ENGRAVED CONTROL PANEL
ADJUSTABLE PULL/TENSION CONTROL W/ BYPASS
LEVELWIND SPEED & DIRECTION CONTROLS
SPRING RETURN TO NEUTRAL JOYSTICK
W/ PAYOUT LOCKOUT
FULL HYDRAULIC SYSTEM CONTROLS & GAUGES
FULL ENGINE CONTROLS & GAUGES

USTOM

DRUM CAPACITY:
31" WIDE
36" RATED DIAMETER
10,600' ROPE CAPACITY
7/16" DIAMETER
DIMENSIONS
198" LONG
96" WIDE
97.5" TALL (SHIELD UP)
83" TALL (SHIELD DOWN)
9.100 LBS.







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.