

## **SHERMAN + REILLY PLW-200X**

Four Drum Turret Pilot Line Winder



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



## **SHERMAN + REILLY PLW-200X**

Four Drum Turret Pilot Line Winder

## **EQUIPMENT SPECS**

**PLW-200X** 

PULLING CAPACITY MAX:: 2,000 RATED AT TOP OF DRUM

AVERAGE LINE SPEED: 3.5 MPH CONTINUOUS TURRET ROTATION: 360 DEGREE, CONTINUOUS REEL CAPACITY: 6,000 FT. 0F 7/16" PE12 ROPE

DRIVE SYSTEM: HYDRAULIC MOTOR, CHAIN AND SPROCKET ENGINE: TIER 4 DIESEL, 49 PEAK HP, WATER COOLED

FUEL CAPACITY: 14 GALLONS
HYDRAULIC FLUID: ISO GRADE 32
HYDRAULIC RESERVOIR: 25 GALLONS

PAYOUT BRAKE: HYDRAULIC DISC-CALIPER, ELECTRONICALLY OVER HYDRAULIC WITH FINITE PSI CONTROL

LEVELWIND: HYDRAULICALLY CONTROLLED, JOYSTICK CONTROLLED (2)

OPERATOR'S SAFETY ENCLOSURE: SAFE-ZONE CAB, OPEN/HALF CAB, TURRET MOUNTED

FRAME CONSTRUCTION: STEEL TUBING, CONTINUOUS WELD

LENGTH (OVERALL, NOM.): 15 FT. WIDTH (OVERALL, NOM.): 8 FT.

HEIGHT (OVERALL, NOM.): 9FT., 10IN. WEIGHT (WITH ROPE): 12,000 LBS.

GVWR: 12,500 LBS.

SUSPENSION: LEAF SPRING AXLE CONFIGURATION: SINGLE

WHEEL CONFIGURATION AND TIRES: SINGLE 245/70R17.5
BRAKES (TRAILER): ELECTRIC, WITH BREAK-AWAY SWITCH

TOWING ATTACHMENT: 3 IN. PINTLE EYE, WITH TWO SAFETY CHAINS AND HOOKS

TIE DOWNS (4): 5/8 IN. DIA. STEEL D-RINGS

STABILIZING JACKS: HYDRAULIC WITH GALVANIZED SHOE (4) FRONT/NOSE JACK: HYDRAULIC WITH GALVANIZED SHOE (1)

ELECTRICAL SYSTEM: 12 VDC BATTERY: 12 VOLT, GROUP 27

LIGHTS/NAVIGATION: US DOT LED, 12 VDC

**GROUNDING (4): 3/4 IN. DIA. COPPER-CLAD STEEL LOOPS (4)** 

WHEEL CHOCKS AND HOLDERS: STANDARD

FIRE EXTINGUISHER: ABC DRUM COVERS: VINYL

**COLOR: S+R WHITE, GALVANIZED** 







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.