



SHERMAN + REILLY T-2608 PULLER-TENSIONER

with 8,000 lb. TENSIONING CAPACITY per BULLWHEEL



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN + REILLY T-2608 PULLER-TENSIONER

with 8,000 lb. TENSIONING CAPACITY per BULLWHEEL

EQUIPMENT SPECS

SPECIFICATIONS:

TENSIONS (2) CONDUCTORS AT ONCE
8,000 LB. MAX TENSIONING CAPACITY, PER BULLWHEEL
SYNCHRONIZED TENSIONING, UP TO (3) MACHINES
PROTECTED, OFF-GROUND OPERATOR POSITION
(2) SETS HYDRAULICALLY-DRIVEN BULLWHEELS FOR 4 TOTAL BULLWHEELS
FULLY ENCLOSED SAFE-ZONE CAB W/ HEATING & COOLING
DIGITAL CONTROLS & SELF-DIAGNOSTICS
4 MPH MAX LINE SPEED
HYDRAULIC, MOTOR-DRIVEN TENSIONING BRAKE
SPRING-APPLIED FAIL-SAFE BRAKE
AUTOMATIC BRAKE CONTROL, PER OPERATOR SETTING
(4) ADJUSTABLE FAIRLEAD ROLLERS, (2) FRONT & REAR
TANDEM AXLE CONFIGURATION TRAILER
3" ADJUSTABLE PINTLE EYE W/ SAFETY CHAINS/HOOKS
(2) HYDRAULIC, ANTI-SLIDE FRONT/NOSE JACKS, W/ SHOES
(2) HYDRAULIC, ANTI-SLIDE CORNER STABILITY JACKS, W/ SHOES
72HP WATER COOLED DIESEL ENGINE
12 GALLON FUEL CAPACITY
20 GALLON HYDRAULIC RESERVOIR
DIMENSIONS:
60" DIAMETER BULLWHEELS
(5) 1" RADIUS GROOVES PER BULLWHEEL
25' OVERALL LENGTH
8' 6" OVERALL WIDTH
10' 4" OVERALL HEIGHT
18,500 LBS.
24,000 LBS. GVWR



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com