



CONDUX TESMEC AFB506 PULLER-TENSIONER

WITH 20,000 lb. TENSIONING CAPACITY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



CONDUX TESMEC AFB506 PULLER-TENSIONER

WITH 20,000 lb. TENSIONING CAPACITY

EQUIPMENT SPECS

DESCRIPTION:

PROVIDES UP TO 20,000 LBS. PULLING AND TENSIONING FORCE AS A SINGLE LINE MACHINE
PROVIDES UP TO 10,000 LBS. PULLING AND TENSIONING FORCE PER SIDE AS A TWO BUNDLE MACHINE
60" BULLWHEELS CAN BE LOCKED TOGETHER OR INDEPENDENTLY OPERATED
BULLWHEELS ARE WEAR-PROOF INTERCHANGEABLE NYLON SECTORS, SPECIFICALLY DESIGNED TO LET THE LINE TURN WHILE GOING THROUGH ELIMINATING "BIRD CAGING" AND WIRE LAY DIRECTION REEVING
NEGATIVE SELF-ACTING BRAKE THAT MAINTAINS LINE TENSION IN THE EVENT THE PULL IS STOPPED OR POWER/HYDRAULIC PRESSURE IS LOST WITH NO OPERATOR ACTION TO INITIATE
HYDRAULIC DYNAMOMETER ALLOWS OPERATOR TO SET PULLING & TENSIONING FORCE IN POUNDS QUICKLY AND ACCURATELY; THIS ALSO ALLOWS
THE OPERATOR TO PULL CONDUCTOR UP TO SAG AFTER PULL

STANDARD EQUIPMENT:

HYDRAULIC TRANSMISSIONS: 2 CLOSED CIRCUIT HYDRAULIC MOTORS FOR STEP-LESS SPEED VARIATION IN BOTH ROTATING DIRECTIONS
LIGHT GEAR - 675 LBS. TO 3,150 LBS.
HIGH GEAR - 1,700 LBS. TO 10,100 LBS.
BULLWHEELS LOCKED TOGETHER DOUBLES VALUES SHOWN
PLANETARY GEARBOXES WITH HIGH, NEUTRAL AND LIGHT GEAR SELECTOR
LIGHT GEAR PROVIDES LOW POWER CONTROL FOR STATIC AND OPGW INSTALLATION
HYDRAULIC TOOL CIRCUITS FOR REEL STANDS OR REEL WINDERS
ONE PERSON CAN OPERATE PULLER-TENSIONER AND REEL EQUIPMENT FROM CONTROL STATION
HYDRAULICALLY ACTUATED LOCKING DRUM CLAMPS, CLAMP ROPE OR CONDUCTOR TO THE BULLWHEEL FOR ENHANCED SAFETY WHEN BULLWHEELS ARE STOPPED

SPECIFICATIONS:

JOHN DEERE 4045HF 4-CYLINDER TURBO DIESEL ENGINE - 86HP NOISE REDUCTION ENGINE COMPARTMENT
TANDEM AXLE SINGLE WHEEL PINTLE HITCH TRAILER
215/75R17.5 TIRES / 8 HOLE RIMS
ELECTRIC TRAILER BRAKES

DIMENSIONS:

WEIGHT: 17,000 LBS
LENGTH: 212"
WIDTH: 102"
HEIGHT: 113"



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com