

SHERMAN + REILLY T7212 PULLER-TENSIONER

WITH 25,000 lb. TENSIONING CAPACITY



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



SHERMAN + REILLY T7212 PULLER-TENSIONER

WITH 25,000 lb. TENSIONING CAPACITY

EQUIPMENT SPECS

STANDARD FEATURES: 12,000 LBS. TENSIONING CAPACITY, PER BULLWHEEL PAIR **4 MPH MAX LINE SPEED** (4) 72" DIAMETER BULLWHEELS, 5 GROOVES EACH 1 1/8" GROOVE RADIUS MOTOR-DRIVEN HYDRAULIC TENSIONING BRAKE **AUTOMATIC BRAKE CONTROL SYSTEM** 80HP DIESEL ENGINE, WATER COOLED 20 GALLON HYDRAULIC RESERVOIR (2) FRONT, (2) REAR QUICK CONNECT EXTERNAL HYDRAULIC CONNECTIONS (2) FRONT, (2) REAR ADJUSTABLE FAIRLEAD ROLLERS **FULLY ENCLOSED CAB W/ A/C & HEAT GENERAL SPECIFICATIONS:** 27' OVERALL LENGTH 8' 6" WIDTH 11' 10" TALL 30,000 LBS. GVWR (2) FRONT, (2) REAR HYDRAULIC JACKS **US D.O.T. LIGHTING CAB-TOP FLOOD LIGHTS** 3/4" COPPER-CLAD STEEL GROUND LOOPS WHEEL CHOCKS







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.