



SHERMAN + REILLY PTR-7230 PULLER-TENSIONER

WITH 25,000 lb. TENSIONING CAPACITY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN + REILLY PTR-7230 PULLER-TENSIONER

WITH 25,000 lb. TENSIONING CAPACITY

EQUIPMENT SPECS

GENERAL SPECIFICATIONS:

30,000 LBS. MAX PULLING CAPACITY

25,000 MAX TENSIONING CAPACITY

4MPH MAX LINE SPEED

112" DIAMETER MAX RE-CONDUCTOR REEL SIZE

84" D X 60" W ROPE REEL

25,000' .84" DIAMETER ROPE CAPACITY

24,250' 20MM DIAMETER CABLE HARDLINE CAPACITY

(2) 72" BULLWHEELS

268HP TURBOCHARGED ENGINE, WATER COOLED

35 GALLON FUEL CAPACITY

20 GALLON HYDRAULIC RESERVOIR

AUTOMATIC TENSIONING BRAKE SYSTEM

FAIL-SAFE BRAKE

FULLY ENCLOSED CLIMATE CONTROLLED CAB

(2) FRONT, (2) REAR HYDRAULIC JACKS

3/4" DIAMETER COPPER-CLAD STEEL LOOP GROUNDING

WHEEL CHOCK

DIMENSIONS:

48' LONG

8' 6" WIDE

12' 2" TALL

63,931 LBS. GVWR



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com