

## **SHERMAN + REILLY PT-3000**

PULLER-TENSIONER



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



## SHERMAN + REILLY PT-3000

PULLER-TENSIONER

## **EQUIPMENT SPECS**

PULLING CAPACITY: 3,000 LB. (RATED AT THE TOP OF DRUM)

**TENSIONING CAPACITY: 2,000 LB.** 

**AVERAGE LINE SPEED: PULLING: 4 MPH** 

MAXIMUM CONDUCTOR REEL SIZE: 66 IN. O.D. X 38 IN. W MAXIMUM REEL WEIGHT: 6,000 LB., WITH CONDUCTOR

SPINDLE DIAMETER: 2-5/8 IN.

DRIVE SYSTEM: HYDRAULIC, DIRECT DRIVE ENGINE: TIER 4 DIESEL, 45 HP, WATER COOLED

**CENTRALIZED ENGINE CONTROLS: CANBUS OPERATING SYSTEM** 

HYDRAULIC FLUID: ISO GRADE 32 HYDRAULIC RESERVOIR: 25 GAL.

FAIL-SAFE BRAKE: SPRING-APPLIED, HYDRAULIC PRESSURE RELEASED

**FUEL CAPACITY: 18 GAL.** 

OPERATOR ENCLOSURE: OPEN/HALF ENCLOSED CAB

FRAME CONSTRUCTION: STEEL TUBING, CONTINUOUS WELD

LENGTH, OVERALL, NOMINAL: 16 FT., 9 IN. WIDTH, OVERALL, NOMINAL: 8 FT., 5 IN. HEIGHT, OVERALL, NOMINAL: 9 FT., 5 IN. NET WEIGHT, NO OPTIONS, NOMINAL: 3,995 LB.

**GVWR: 10,000 LB.** 

SUSPENSION: LEAF SPRING

WHEEL CONFIGURATION & TIRES: DUAL, 235/85 R16

**AXLE CONFIGURATION: SINGLE** 

BRAKES, TRAILER: ELECTRIC, WITH BREAK-AWAY SWITCH

FRONT/NOSE JACKS: HYDRAULIC

**REAR JACKS: 2 HYDRAULIC** 

TOWING ATTACHMENT: 3 IN. ADJUSTABLE PINTLE EYE

**SAFETY CHAINS: 2 EACH, WITH HOOK** 

**ELECTRICAL SYSTEM: 12 VDC** 

BATTERY: 12 V, LED, U.S. DOT-APPROVED

**GROUNDING: FOUR 3/4 IN. DIAMETER COPPER-CLAD STEEL LOOPS** 

TIE DOWNS: TWO 5/8 IN. DIAMETER STEEL D-RINGS

TIE OFF POINT: TIE OFF POINT AT REAR BUMPER, 3,000 LB. AT 45°

FIRE EXTINGUISHER: ABC

PAINT: S+R WHITE

PAYOUT BRAKE: HYDRAULIC WITH ELECTRIC CONTROLS LEVELWIND: OVERHEAD / UNDERGROUND HYDRAULIC



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.