



CONDUX TESMEC FRB616

HYDRAULIC TENSIONER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



CONDUX TESMEC FRB616

HYDRAULIC TENSIONER

EQUIPMENT SPECS

TENSIONER PERFORMANCE

MAX TENSION: 15,750 LBF (2 X 70 KN)

OR 31,500 LBF (1 X 140 KN)

MAX SPEED: 3.1 MPH (5 KM/H): PULL-BACK PERFORMANCE

MAX PULL: 15,750 LBF (2 X 70 KN)

OR 31,500 LBF (1 X 140 KN)

MAX SPEED: 0.4 MPH (2 X 0.7 KM/H)

NOTE: THE BASIC MACHINE PERFORMANCE IS CALCULATED AT 68°F (20°C) AND AT SEA LEVEL

CHARACTERISTICS

BULL-WHEEL DIAMETER: 67 IN (1,702 MM)

MAX CONDUCTOR DIAMETER: 1 13/16 MM (46 MM)

WEIGHT: 16,755 LBS (7,600 KG)

ENGINE

DIESEL: 64 HP (48 KW)

COOLING SYSTEM: WATER

ELECTRICAL SYSTEM: 24 V

HYDRAULIC TRANSMISSION

2 HYDRAULIC HALF-CLOSED CIRCUITS THAT ALLOW VERY SENSITIVE TENSIONING CONTROL AND NEGLIGIBLE DEVIATIONS OF TENSION IN CASE OF SPEED CHANGE. THE MACHINE IS PROVIDED WITH TENSION PRE-SETTING SYSTEM.

GENERAL SPECIFICATIONS

NET WEIGHT: 20,750 LBS (9,410 KG)

OVERALL LENGTH: 236 IN (6,000 MM)

OVERALL WIDTH: 96 IN (2,440 MM)

HEIGHT: 135 IN (3,430 MM)



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com