

HOGG & DAVIS ODP-60 SINGLE DRUM PULLER

WITH 6,000 LB. FULL DRUM CONTINUOUS LINE-PULL



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



HOGG & DAVIS ODP-60 SINGLE DRUM PULLER

WITH 6,000 LB. FULL DRUM CONTINUOUS LINE-PULL

EQUIPMENT SPECS

PERFORMANCE:

CONTINUOUS LINEPULL RATING: 6,000 LBS
CONTINUOUS TORQUE RATING: 174,000 IN-LB
INFINITELY VARIABLE SPEED FROM 0.0 - 4.2 MPH

TRAILER DATA:

TANDEM 8,000 LB LEAF-SPRUNG AXLES 17,600 LB GVWR ELECTRIC TRAILER BRAKES
(3) DROP-LEG MANUAL LEVELING JACKS
(4) R17.5 - 16 PLY RATED TIRES
FULL COVERAGE FENDERS WITH MUDFLAPS
D.O.T. TRAILER LIGHTING W/7-WIRE CONNECTOR

DRIVE SYSTEM:

99.0 HP DIESEL ENGINE
CLOSED LOOP HYDROSTATIC HYDRAULIC DRIVE
SPRING APPLIED, HYDRAULIC RELEASE DRIVE TRAIN BRAKE
MECHANICAL CLUTCH DRUM ENGAGEMENT
STANDARD: FREEWHEEL DISCONNECT
16" DIA. VENTILATED OVERSPIN BRAKE

GENERAL FEATURES:
19 GALLON FUEL CAPACITY
29.5 GALLON HYDRAULIC OIL CAPACITY
HYDRAULIC BOOM LEVELWIND
LOCKABLE STEEL BATTERY BOX

DRUM CAPACITY: RATED DIAMETER: 58" WIDTH: 44"

RATED ROPE CAPACITY: 15,160 FEET (3/4" DIA.)

UNIT DIMENSIONS: LENGTH: 17'6" WIDTH: 8'6"

HEIGHT (SHIELD UP): 9'4-1 /4" HEIGHT (SHIELD DOWN): 8'1-3/4" WEIGHT (CURB): 11,000 LBS







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com