



SHERMAN + REILLY P-2000X SINGLE DRUM PULLER

WITH 20,000 lb. PULLING CAPACITY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



SHERMAN + REILLY P-2000X SINGLE DRUM PULLER

WITH 20,000 lb. PULLING CAPACITY

EQUIPMENT SPECS

FULLY HYDRAULIC/DIRECT DRIVE SYSTEM

175 HP INDUSTRIAL DIESEL ENGINE

(4) HYDRAULIC JACKS FOR LEVELING

CENTRALIZED ENGINE CONTROLS - CAN-BUS TECHNOLOGY

4 MPH AVG LINE PULLING SPEED

DIGITAL CONTROLS W/ REAL TIME MONITORING

22,000' 20MM ANTI-TWIST BRAIDED WIRE ROPE

.92 LBS./ FT. - 58,900 LBS. MIN BREAK STRENGTH

ELECTRICALLY ACTUATED, AUTO CONTROLLED LEVELWIND

SAFE-ZONE CAB, FULLY ENCLOSED/ SINGLE DOOR

TRI-AXLE CONFIGURATION

ADJUSTABLE PINTLE EYE, W/ (2) SAFETY CHAINS & HOOKS

(4) STEEL D-RING TIE DOWNS

(2) 12V, 720 CCA BATTERIES

DOT-APPROVED 12V LED LIGHTS

(4) 3/4" DIA COPPER-CLAD STEEL GROUNDING LOOPS

ELECTRIC BRAKE TRAILER

DIMENSIONS:

23' 8" OVERALL LENGTH

8' 6" WIDTH

10' 10" HEIGHT

45,000 LBS. W/ ROPE

50,000 LBS. GVWR

HARDLINE REEL: 30" DIAM CORE, 76" OUTSIDE WIDTH, 50"

INSIDE WIDTH

76" FLANGE DIAMETER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com