

TSE DPT 60

SINGLE DRUM PULLER



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



TSE DPT 60

SINGLE DRUM PULLER

EQUIPMENT SPECS

HYDRAULIC OVERHEAD LEVELWIND.

6052 HEAVY DUTY PULLING DRUM.

HYDRAULIC FRONT JACK.

COMBINATION OVERHEAD/UNDERGROUND LEVELWIND.

UNDERGROUND PULLING DRUM.

BR-6030 BREAKAWAY REEL.

MODEL DPT-60	
CONTINUOUS TORQUE RATING	180,000 INLBS
CONTINUOUS LINEPULL RATING	6,000 LBS.
*MAXIMUM LINESPEED	0-4 MPH

DPIOUB	
UNIT LENGTH	17'-5"
UNIT WIDTH	7'-8"
UNIT HEIGHT	7'-2"
UNIT WEIGHT	9.150 LBS. (APPROX.)

STANDARD FEATURES

DDT/OD

- •PROVEN HYDROSTATIC PULLING AND TENSIONING SYSTEM WITH HYDRAULIC OIL COOLER.
- 115 HP WATER-COOLED DIESEL ENGINE.
- REEL CAPACITY UP TO 72" DIAMETER, 52" WIDE AND 6,000 LBS.
- REEL SHAFT DIAMETER OF 3-1/2".
- TANDEM AXLE WITH LEAF SPRING SUSPENSION.
- INFINITELY VARIABLE LINESPEED AND LINEPULL CONTROL.
- FREE WHEELING DISCONNECT FOR HIGH SPEED ROPE PULL OUT.
- SPRING APPLIED-HYDRAULIC PRESSURE RELEASED HOLDING BRAKE.
- CENTRAL OPERATOR'S POSITION FOR MAXIMUM SAFETY AND VISIBILITY.
- QUICK CHANGE REEL SHAFT WITH STRAIGHT VERTICAL LIFT.
- ENGRAVED OPERATOR'S CONSOLE.



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.