



# SHERMAN + REILLY DDHX-75-T UNDERGROUND PULLER

HYDRAULIC DUCT DAWG WITH 7,500 LBS. MAX. PULLING CAPACITY



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)



# SHERMAN + REILLY DDHX-75-T UNDERGROUND PULLER

HYDRAULIC DUCT DAWG WITH 7,500 LBS. MAX. PULLING CAPACITY

## EQUIPMENT SPECS

**PULLING CAPACITY MAX : 7,500 LB**  
**BULLWHEELS : TWIN CAPSTAN, 6 IN. DIA., 5-GROOVE FOLLOWED BY 6-GROOVE**  
**GEARBOX & LINE SPEED**  
**1ST GEAR 0-60 FPM @ 7,500 LB WITH DEMAND PAYOUT**  
**2ND GEAR 0-120 FPM @ 3,500 LB WITH DEMAND PAYOUT**  
**3RD: 0-285 FPM @ 1,500 LB WITH DEMAND PAYOUT**  
**DRIVE SYSTEM : HYDRAULIC**  
**HYDRAULIC FLUID : ISO GRADE 32**  
**HYDRAULIC RESERVOIR : 25 GALLONS WITH COLD WEATHER PACKAGE OPTIONAL**  
**ENGINE : 42 HP, DIESEL, WATER-COOLED, ELECTRIC START**  
**FUEL CAPACITY : 13 GALLONS**  
**PULLING ROPE : 3/8 IN., 6 X 25 XIP IWRC STEEL WIRE ROPE, 2,000 FT**  
**BOOM : HYDRAULIC, JOYSTICK CONTROLLED, 3-AXIS, >50 DEGREE SWING ARC - 17 IN. SHEAVE W/ 60 DEGREE SWIVEL HEAD**  
**LEVELWIND : DUAL AUTOMATIC FAIRLEAD SHEAVES**  
**PULLER MOUNTED CONTROLS : HYDRAULIC OVERRIDES; JACKS, BOOM**  
**PULLER WIRELESS CONTROLS : CANBUS CONTROLLER COMMUNICATING W/ RADIO CONTROLLED REMOTE, 300 FT. MA**  
**FOOTAGE COUNTER : ELECTRONIC, ACTUAL FOOTAGE, PAY-IN AND PAY-OUT WITH MEMORY**  
**HYDRAULIC TOOL CIRCUIT : OPTIONAL - 7 GPM @ 2,500 PSI AUXILIARY**  
**PULLING CONNECTORS : ROTATION-RESISTANT: (1) RATED AT 3,000 LB & (1) RATED AT 8,800 LB**  
**FRAME CONSTRUCTION : STEEL TUBING, CONTINUOUS-WELD**  
**LENGTH, OVERALL, NOMINAL : 186 IN.**  
**WIDTH, OVERALL, NOMINAL : 95 IN.**  
**HEIGHT, OVERALL, NOMINAL : 114 IN.**  
**WEIGHT : NOMINAL 5,000 LB W/OUT ROPE - 7,200 LB WITH ROPE**  
**GVWR : 8,800 LB**  
**SUSPENSION : LEAF SPRING**  
**AXLE CONFIGURATION : SINGLE**  
**WHEEL CONFIGURATION & TIRES : SINGLE, LT235/75R17.5**  
**BRAKES, TRAILER : ELECTRIC, WITH SAFETY BREAK-AWAY SWITCH**  
**TOWING ATTACHMENT : 3 IN. ADJUSTABLE PINTLE EYE**  
**SAFETY CHAINS : 2 EA., WITH HOOKS**  
**TIE-DOWNS : 5/8 IN. DIAMETER STEEL D-RINGS**  
**FRONT / NOSE JACK : HYDRAULIC, WITH SHOE - 144 IN. SQUARE OF SURFACE AREA**  
**STABILIZING JACKS : HYDRAULIC, WITH SHOE AT REAR COMERS - 144 IN. SQUARE OF SURFACE AREA**  
**ELECTRICAL SYSTEM : 12 VDC, 60 AMP ALTERNATOR**  
**LIGHTS, NAVIGATION : US DOT LED, 12 VDC**  
**BATTERY : 12 V**  
**GROUNDING : 3/4 IN. DIA. COPPER-CLAD STEEL GROUND LOOPS (4)**  
**FIRE EXTINGUISHER : ABC**  
**COLOR : WHITE**



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

**888-925-0858**  
**www.customtruck.com**