

CONDUX TESMEC RW23 WINDER SKID

WITH 45,000 LBS. MAXIMUM GVWR



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL



CONDUX TESMEC RW23 WINDER SKID

WITH 45,000 LBS. MAXIMUM GVWR

EQUIPMENT SPECS

DESCRIPTION:

RW23 HYDRAULIC REEL WINDER TRAILER IS DESIGNED TO WORK WITH THE CONDUX-TESMEC PULLERS & PULLER/TENSIONERS. IT CAN ALSO BE OPERATED INDEPENDENTLY WITH A HYDRAULIC POWER PACK. IT IS EQUIPPED WITH AN AUTOMATIC LEVELWIND AND NEGATIVE SELF-ACTING HYDRAULIC BRAKE. HYDRAULIC CONTROLS FOR COMPLETE REEL CONTROL WITH FREEWHEEL. ONLY CONDUX-**TESMEC HD FIXED WIRE ROPE REELS ARE** INTERCHANGEABLE.

STANDARD EQUIPMENT:

TANDEM AXLE, SPRING SUSPENSION, DUAL WHEEL, AIR BRAKE TRAILER. 45,000 GVWR, 235/75R17.5 TIRES, ADJUSTABLE PINTLE HITCH, HYDRAULIC CONTROL STATION WITH DRIPLESS HYDRAULIC QUICK COUPLERS, THREE 50' HYDRAULIC HOSES, MANUAL AND AUTOMATIC LEVELWIND, GROUNDING ATTACHMENTS, ANCHOR POINTS, 36"X 15"X 20" ALUMINUM TOOL BOX

SPECIFICATIONS:

REEL WITH 18MM X 22,000' ANTI-TWIST WIRE ROPE **18MM FUH HIGH TECH ANTI-TWISTING BRAIDED** WIRE ROPE, FUX IS MADE WITH HIGH TENSILE STRENGTH **GALVANIZED STEEL STRANDS ALLOWING HIGHER WORKING** AND BREAKING LOAD WITH THE SAME LINEAR MASS. HIGH FLEXIBILITY, COMPLETE STABILITY TO ROTATION, DISTRIBUTION OF **BETWEEN STRAND WIRES.** 18MM = 11/16", 0.68 LBS. PER FT., MINIMUM BREAKING LOAD-54.629 LBS. 22,000' OF 18MM PLUS REEL = 18,000 LBS. (EMPTY REEL = 3,000 LBS. - 75" TALL X 45" WIDE) TRAILER WEIGHT WITH 18MM ANTI-TWIST - 23,000 LBS.

DIMENSIONS:

on the date of this publication.

4.500 LBS. - WEIGHT W/O REEL 194" LONG 100" WIDE 125" HIGH



888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL





