



CONDUX TESMEC RW24 WINDER SKID

WITH 20,000 LBS. CAPACITY



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com



CONDUX TESMEC RW24 WINDER SKID

WITH 20,000 LBS. CAPACITY

EQUIPMENT SPECS

DESCRIPTION:

URW24 HYDRAULIC WINDER IS DESIGNED TO WORK WITH THE CONDUX-TESMAC PULLERS & PULLER-TENSIONERS AND CAN OPERATE AS A SEPARATE WINDER SYSTEM WITH POWER PACK. IT IS EQUIPPED WITH AN AUTOMATIC AND MANUAL LEVELWIND SYSTEM. NEGATIVE SELF-ACTING HYDRAULIC BRAKE. HYDRAULIC CONTROLS FOR COMPLETE REEL CONTROL WITH FREEWHEEL. RW24 CAN BE USED WITH; FIXED PULLING REEL W/ ROPE, DETACHABLE SPLIT PULLING REEL, STEEL OR WOOD REELS.

SPECIFICATIONS:

FORKLIFT PICKING POCKETS, LIFTING EYES/ANCHOR POINTS, GROUNDING POINTS, HYD. CONTROL STATION WITH (3) 40' HYDRAULIC CONNECTING HOSES WITH DRIPLESS FITTINGS AND STORAGE RACK. PRESSURE RELEASE DEVICE, 3" ARBOR BAR WITH 5" ADAPTERS, LEVELWIND.

MAXIMUM REEL CAPACITY:

45" WIDE
90" HIGH
20,000 LB. CAPACITY

DIMENSIONS:

106" LONG
96" WIDE
66" TALL W/O REEL
86" TALL W/ CONDUX SPLIT REEL
3,000 LBS.



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858
www.customtruck.com