

## LOAD KING 2,000 GALLON WATER TANK AVAILABLE ON A VARIETY OF CHASSIS BRANDS & MODELS



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



## LOAD KING 2,000 GALLON WATER TANK

AVAILABLE ON A VARIETY OF CHASSIS BRANDS & MODELS

## **EQUIPMENT SPECS**

**CAPACITY: 2,000 US GALLONS** 

DIMENSIONS: 98" LONG X 96" WIDE X 64.75" TALL

**TANK SHELL: A36 STEEL** 

TANK ENDS: A36 STEEL. DOMED WITH FLANGE

**TEAR PAD: A36 STEEL** 

TANK BAFFLES: (1) A36 STEEL W/ 20" CRAWL HOLE TANK RUNNERS: A36 STEEL, FORMED ANGLE

STYLE, FULL LENGTH

TANK SHAPE: MODIFIED ELLIPSE, LARGE RADIUS CORNERS

MAN-WAY: 24" ROUND MAN-WAY, MESH

LIFT OUT GRATE, NO LID

FILL PIPE: 2-1/2" PIPE AND CAM GROOVE COUPLER
LADDER: REAR MOUNTED, PIPE CONSTRUCTION,
ANTI-SLIP RUNGS FENDERS: A36 STEEL, SPRAY
LINED FINISH, BLACK ONLY, TROUGH STYLE TRAY
MEDIA BLAST SURFACE, PRIMER, AND TOP COAT TANK WHITE

(ADDITIONAL COLORS AVAILABLE AT AN UP-CHARGE), TANK INTERIOR COATED (STANDARD)

**WATER PUMP:** 

**4X3 SHAFT DRIVEN WATER PUMP** 

PT0

**INCLUDES REQUIRED FITTINGS FOR CHASSIS WITH AIR BRAKES** 

FRONT SPRAY SYSTEM:

(2) INDEPENDENTLY OPERATED AIR SPRAY VALVES

MID SPRAY SYSTEM:

(1) INDEPENDENTLY OPERATED AIR SPRAY VALVE LOCATED DRIVER SIDE (PASSENGER SIDE OPTIONAL)

**REAR SPRAY SYSTEM:** 

(2) INDEPENDENTLY OPERATED AIR SPRAY VALVES

**ON-ROAD WATER TANK PARTS** 

**TIE DOWN HARDWARE AND MISC PARTS** 

**HOSE REEL ASSEMBLY:** 

1-1/2" X 50' MANUAL HOSE REEL MOUNTED AT

REAR OF TRUCK, WITH 50' HOSE AND ADJUSTABLE NOZLE

**ELECTRICAL AND LIGHTING** 

**DOT/ICC COMPLIANT LIGHTS & REFLECTORS** 

TRUCK-LITE WIRING HARNESS

2-1/2" X 50' WATER TRUCK HYDRANT HOSE

3" SUCTION HOSE KIT CONTAINS:

(2) 3" X 10' MXF CAM & GROOVE

(1) 3" X 10' FEMALE CAM & GROVE X 3" SUCTION STRAINER







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.