

## LOAD KING PREMIER FIBERGLASS ROOFING CONVEYOR

AVAILABLE FROM 31-43'



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



## LOAD KING PREMIER FIBERGLASS ROOFING CONVEYOR

AVAILABLE FROM 31-43'

## **EQUIPMENT SPECS**

**HEAD SECTION:** 

ALL ALUMINUM CONSTRUCTION W/ 1/4" BELT LAGGING FOUR BOLT PILLOW STYLE BEARING HOLDERS

STAINLESS STEEL SUPPORT PLATES & HINGED COVER

**EMERGENCY STOP** 

TAIL SECTION:

ALL STAINLESS STEEL CONSTRUCTED GUARDS,

**UTILIZES A STEEL V-GUIDED BELT PULLY** 

OPTION:

**ALUMINUM & STEEL COMBO OR ALL STEEL -**

24' - 28' OVERALL BED SPACE

**CRADLE:** 

17' STEEL 1-PIECE HEAVY DUTY CONSTRUCTION,

SUPPORTS CONVEYOR OR FRAME STRUCTURE

BELT:

**PVC NON-CONDUCTIVE BELTING** 

**STAINLESS STEEL PADDLES** 

**BELT SPEED = 60' A MINUTE** 

**CROSS SUPPORTS:** 

**STAINLESS STEEL CONSTRUCTION -**

RUBBER - COATED RETURN IDLER WHEELS EQUIPPED W/ BEARINGS

HYDRAULIC HOSE ROUTING THROUGHOUT FRAME STRUCTURE IS CAPTIVE IN HOLDERS

ALL STAINLESS STEEL HARDWARE, BOLTS, NUTS, ETC. HYDRAULIC STABILIZERS

360° ROTATION ERGONOMIC CONTROLS

ROTATIONAL GEAR BOX IS FIXED FOR LONGER HOSE LIFE

10' INTEGRATED SUB-BASE & MOUNTING DECK DESIGNED TO CARRY OPTIONAL FORKLIFT KIT

MAST CLEARANCE UP TO 70" BELT LOADED HEIGHT 18" +

**FLUSH MOUNTED ROTATION COVER FOR EASIER** 

ACCESS TO ROTATION SYSTEM, NO STEEL PLATE TO TRIP OVER







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.