

ELLIOTT D86 DIGGER DERRICK

UTILITY TRANSMISSION LINE DIGGER



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL



ELLIOTT D86 DIGGER DERRICK

UTILITY TRANSMISSION LINE DIGGER

EQUIPMENT SPECS

SHEAVE HEIGHT (MAXIMUM): 86'/26,2 M SHEAVE HEIGHT (RETRACTED): 40'/12,2 M HORIZONTAL REACH (MAXIMUM): 73'/22,3 M HORIZONTAL REACH (INTERMEDIATE): 50'/15,2 M HORIZONTAL REACH (RETRACTED): 26'/7,9 M LIFTING CAPACITY (MAXIMUM): 50,000 LBS/22 679 KG LIFTING CAPACITY @ 10' RADIUS: 30,000 LBS/13 608 KG **BOOM ELEVATION LIMITS: -8/+80 DEGREES** WINCH SINGLE LINE PULL: 12,000 LBS/5443 KG **BOOM ROTATION: 360 DEGREES CONTINUOUS** DIGGER MOTOR TORQUE: 20,000 FT-LB/27 116 NM DIGGER SPEED (HIGH/LOW): 80 RPM / 35 RPM DIGGING RADIUS (MAXIMUM): 41'/12,5 M DIGGING RADIUS (MINIMUM): 24'/7,3 M **OUTRIGGER CONFIGURATION: OUT-DOWN RECOMMENDED GVWR: 20'/6,1 M** OUTRIGGER SPREAD (MID-SPAN): 13'11"/4,2 M **CERTIFICATION: ANSI A10.31 FOR DIGGER DERRICKS**







*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL