



SPECS

GENERAL DESCRIPTION: 24,000 LB. CAPACITY TAG-ALONG TRAILER WITH BEAVERTAIL & RAMPS.

LOAD CAPACITY: 24,000 LBS. AT 65 M.P.H. (G.V.W.R. 30,250 LBS.)

OVERALL LENGTH: 29'-0"

DECK LENGTH: 24'-0" (19'-0" FLAT DECK + 5'-0" BEAVERTAIL)

DECK WIDTH: 8'-0"

DECK HEIGHT: 34" UNLOADED

FRAME CONSTRUCTION: PIERCED MAINBEAM CONSTRUCTION WITH ONE PIECE INTERLOCKING CROSSMEMBERS.

MAINBEAMS: W12" X 16 LBS. PER FT., GRADE 50 HI-TENSILE.

CROSSMEMBERS: 6" I-BEAM X 3.7 LBS PER FT., GRADE 50 HI-TENSILE ON 18" CENTERS.

SIDERAILS: C8" X 11.5 LBS. PER FT. GRADE 50 HI-TENSILE.

HEADBOARD: 8" CHANNEL, FULL WIDTH OF TRAILER.

DECKING: 2" NOMINAL OAK SECURED TO CROSS-

MEMBERS WITH 5/16" TORQUE SCREWS.

STANDARD PAINT: BLACK ACRYLIC ENAMEL.

(OPTIONAL COLORS AVAILABLE)

RUST PROHIBITIVE UNDERCOATING.

SUSPENSION: HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD AXLE TRACKING ADJUSTMENT, 44,000 LB. CAPACITY.

AXLES: (2) DEXTER 12,000 LB. CAPACITY WITH OIL BATH HUBS.

BRAKES: 12-1/4" X 5" ELECTRIC

WHEELS: 8 HOLE STEEL DISC.

TIRES: 235/80R16, (E), CAP: 3,000 LBS EACH.

RAMPS: 58" X 21.5" TRACTION WITH SPRING ASSIST.

JACK: 12,000 LB. DROPLEG, SIDE CRANK.

HITCH: 4 POSITION CAST STEEL PINTLE EYE, 1-5/8" STOCK, 2-7/8" I.D.

TIE DOWNS: (8) HEAVY DUTY D-RINGS, 4 PER SIDE.

LIGHTS: 12 VOLT DOT & ICC APPROVED. ALL LIGHTS ARE LED TYPE AND FLUSH

MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN FLEXIBLE NEOPRENE JACKET AND MODULAR IN DESIGN. 7 WAY PLUG.



833-955-7732
www.loadkingmfg.com

LOAD KINGTM
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.