



SPECS

40,000 LB CAPACITY TAG-ALONG TRAILER WITH BEAVERTAIL & RAMPS

LOAD CAPACITY: 40,000 LB AT 55 MPH. (G.V.W.R. 47,350 LBS)

OVERALL LENGTH: 30'-0"

DECK LENGTH: 24'-0" (19'-0" FLAT DECK + 5'-0" BEAVERTAIL)

DECK WIDTH: 96"

DECK HEIGHT: 36" UNLOADED

FRAME CONSTRUCTION: PIERCED MAIN BEAM CONSTRUCTION
WITH ONE-PIECE INTERLOCKING CROSS MEMBER.

MAINBEAMS CHASSIS: W14" X 22LBS. PER FT., GRADE 50 HI-TENSILE

CROSSMEMBERS: 6" I-BEAM X 3.7 LBS PER FT. GRADE 50 HI-TENSILE

ON 22" CENTERS. 3/16" STEEL FABRICATED KNEE BRACING ON EVERY OTHER
CROSSMEMBER.

SIDERAILS: C8" X 11.5 LBS. PER FT. GRADE 50 HI-TENSILE.

HEADBOARD: 8" CHANNEL, FULL WIDTH OF TRAILER

DECKING: 1 1/2" APITONG DECKING SECURED WITH CARRIAGE BOLTS & CLIPS

SUSPENSION: HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD AXLE TRACKING
ADJUSTMENT - 44,000 LB CAPACITY

AXLE: (2) AXN 22,500 LB. CAPACITY WITH OIL BATH HUBS.

BRAKES: 12 1/4" X 7 1/2" AIR BRAKES WITH "WABCO" ANIT-LOCK BRAKING SYSTEM AND
SPRING PARKING BRAKES

WHEELS: 10-HOLE STEEL DISC

TIRES: (8) 215/75R17.5, (H)

RAMPS: 60" X 22 1/2" SELF-CLEANING WITH SPRING ASSIST

PARKING JACK: 25,000 LB. DROP LEG, SIDE CRANK

HITCH: 4 POSITION CAST STEEL PINTLE EYE, 1-5/8" STOCK, 3" I.D. 4 BOLT

TIE DOWNS: HEAVY DUTY D-RINGS, 4 PER SIDE

SAFETY CHAINS: (2) 1/2" PLATED HI-TEST

LIGHTS: 12-VOLT DOT & ICC APPROVED. ALL LIGHTS ARE SEALED
BEAM TYPE AND FLUSH MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN
FLEXIBLE NEOPRENE

JACKET AND MODULAR IN DESIGN FOR EASE OF MAINTENANCE. 7 WAY PLUG

MICRO NOVA CLEARANCE LIGHTS, DUAL INTENSITY AT REAR

PAINT: SANDBLAST, EPOXY PRIMER, URETHANE PAINT



833-955-7732
www.loadkingmfg.com

LOAD KING
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.