



SPECS

25-TON CAPACITY TAG-ALONG TRAILER WITH TILTING PLATFORM AND STATIONARY DECK

LOAD CAPACITY: 50,000 LBS. / 25 TONS

OF AXLES: 3

OVERALL LENGTH: 37'-4"

DECK LENGTH: 26' TILTING PLATFORM, 4' STATIONARY DECK

DECK WIDTH: 8'6"

DECK HEIGHT: 38" UNLOADED

LIGHTING: 12V DOT & ICC APPROVED. ALL LIGHTS ARE LED TYPE AND FLUSH-MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN FLEXIBLE NEOPRENE JACKET AND MODULAR IN DESIGN. 7-WAY PLUG. GROTE MICRO-NOVA DUAL INTENSITY LED LIGHTING.

DECKING: STANDARD APITONG DECKING ILO ROUGH-CUT OAK

PAINT: 2-PART EPOXY PRIMER PAINT

HEAVY-DUTY SPRING-ASSISTED RAMPS FOR BETTER DURABILITY & EASE OF USE

REDESIGNED NECK FOR MORE DURABILITY & STREAMLINED APPEARANCE

FRAME CONSTRUCTION: PIERCED MAINBEAM CONSTRUCTION WITH 1-PIECE INTERLOCKING CROSSMEMBERS

HITCH: 4-POSITION CASTS STEEL PINTLE EYE, 1-5/8" STOCK, 3" I.D.

TIE-DOWNS: (8) HEAVY-DUTY D-RINGS, 4 PER SIDE

SUSPENSION: HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD

AXLE TRACKING ADJUSTMENT, 44,000 LB. CAPACITY

WHEELS: 8-HOLE HUB-PILOTED DISC



833-955-7732
www.loadkingmfg.com

LOAD KING
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.