



SPECS

MAXIMUM REEL CAPACITY:

(4) – 8,650 LBS. EACH X 84" TALL X 60" WIDE

CAPACITY:

41,400 LBS. GVWR-CALCULATED AT 15% WEIGHT TRANSFER TO TOW VEHICLES

34,700 LBS. LOAD CAPACITY

DIMENSIONS:

OVERALL LENGTH: 34' 6"

OVERALL WIDTH: 101.5"

76.5" TALL W/O REEL

10' 3" TALL WITH 84" REEL

WEIGHT: 6,700 LBS.

REEL CAPACITY:

(4) – 8,650 LBS. X 84"D X 60"W X 2 5/8" ARBOR BAR

ARBOR LOCK:

SAFELOCK TECHNOLOGY ARBOR LOCKS

NO PINS, OR TOOLS REQUIRED

ONE HANDED OPEN & CLOSE

AXLES:

TRIPLE 12,000# HEAVY DUTY DEXTER SPRING AXLES

ELECTRIC BRAKES ON ALL WHEELS

(6) SIX 235/75R17.5 LR-H TIRES

(1) PAIR MUD FLAPS

REEL RACKS:

(4) FOUR - FIXED 3" X 3" SQUARE ¼" THICK WALL HD BOX TUBING

(4) FOUR - 2 7/8" REEL BARS WITH CROSSARM AND (1) ONE LOCKING COLLAR

REEL BRAKES: (4) 16" BRONZE VENTILATED DISCS WITH MANUAL CALIPER "TRUE STOP" SELF-COOLING TENSION BRAKE

TONGUE, HITCH & JACK:

6" X 3" - ½" WALL, TUBULAR STEEL A-FRAME 6-POSITION ADJUSTABLE HITCH PLATE (14" THROUGH 27")

2 1/2" LUNETTE EYE 42K CAPACITY

3/8" X 36"L ZINK PLATED GRADE 70 SAFETY CHAINS WITH SAFETY HOOKS

(1) 12,000 LB. DROPLEG JACK - TONGUE

(2) 12,000 LB. DROPLEG JACK - REAR CORNER STABILIZERS

WEATHER PROOF HOLDER FOR OPERATORS MANUAL

MAIN FRAME: 6" X 3" - ½" THICK WALL TUBULAR STEEL MAIN FRAME, 4" STEEL CHANNEL CROSSMEMBERS

FENDERS:

FABRICATED 1/8" STEEL DIAMOND TREAD PLATE FENDERS

12 VOLT WIRING SYSTEM:

ICC & DOT APPROVED LED LIGHTS SEALED BEAM RUBBER MOUNTED LED STOP, TURN, TAIL & MARKER LIGHTS

32" PIGTAIL W/ELECTRICAL PLUG, TERMINATED AT JUNCTION BOX BREAKAWAY KIT WITH SEALED LEAD ACID BATTERY & TRICKLE CHARGER

FINISH:

3 STEP TRIPLE HOT DIPPED GALVANIZED FINISH - 10 YEAR STRUCTURAL WARRANTY

2" RED/WHITE REFLECTIVE TAPE



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

