

POSI-PLUS 1600 CABLE HANDLER

WINCH PULLS UP TO 25,000 LBS.



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.



POSI-PLUS 1600 CABLE HANDLER

WINCH PULLS UP TO 25,000 LBS.

EQUIPMENT SPECS

CABLE HANDLERS PROVIDE HIGH PAYLOAD

CAPACITY AND POWERFUL TORQUE FOR FAST

AND EFFICIENT OVERHEAD TENSIONING AND

UNDERGROUND APPLICATIONS, PLUS DURABILITY

FOR EXTENDED LIFECYCLE.

REEL DIAMETER: 48" - 108"

REEL WIDTH: 38" - 68"

REEL DRIVE ROTATION SPEED: 0 TO 18 RPM

PAYLOAD (SUBJECT TO LOCAL REGULATIONS): 20,000 LBS.

PULLING WINCH CAPABILITIES: UP TO 25,000 LBS.

RADIAL PISTOL REEL DRIVE MOTORS:

OUTPUT TORQUE OF 285,000 INCH POUND

REEL MOUNTED, DIRECT DRIVE MOTORS

INTERNAL MULTI-DISC LOAD HOLDING BRAKES

FREEWHEELING CAPABILITY

VARIABLE SPEED

RADIO CONTROL SYSTEM:

HAND HELD REMOTE CONTROL (TRANSMITTER)

MASTER CONTROL PANEL (RECEIVER)

PRECISE CONTROL OF OPERATIONAL FUNCTIONS

ALL FUNCTIONS OPERATED FROM THE PENDANT

SELF-DIAGNOSTIC SYSTEM, SIMPLE EASY MAINTENANCE

PULLING AND FOOTAGE COUNTER

OPTIONAL RECORDING AND REPORT OF PRESSURE AND FOOTAGE VALUES 25,000 LB CONSTANT PULL WINCH AVAILABLE

ELECTRICAL HARNESS TO OPERATE







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.