





*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL



EQUIPMENT SPECS

SPECIFICATIONS MAXIMUM CONTINUOUS TENSION 10,000 LBS. @ 4 MPH BULLWHEEL DIAMETER 72 INCHES GROOVE DIAMETER 2.125 INCHES NUMBER OF GROOVES 5 PER BULLWHEEL

DIMENSIONS (APPROX) LENGTH 211 INCHES WIDTH 89 INCHES HEIGHT 134 INCHES WEIGHT 7,000 LBS.

STANDARD EQUIPMENT PRECISE HYDRAULIC CONTROL WITH ANTI-SURGE ACCUMULATOR TILTED BULLWHEELS TO REDUCE CABLE TWIST 44" BRONZE DISC BRAKES CENTRAL ELEVATED OPERATORS PANEL WITH TENSION CHART 3 ROLLER TAIL FAIRLEAD TANDEM AXLE TRAILER WITH ELECTRIC BRAKES FRONT AND REAR DROP-LEG JACKS TIE DOWN LUGS









*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL