



**TEREX TL80**  
TRANSMISSION AERIAL DEVICE

**IMAGE  
COMING  
SOON**



# SPECS

## TL80:

BOTTOM OF PLATFORM: 75.0 FT (22.9 M)  
WORKING HEIGHT: 80.0 FT (24.4 M)  
HORIZONTAL REACH: 47.2 FT (14.4 M)  
BOTTOM OF PLATFORM TO GROUND: .92 IN. (2.3 CM)  
UPPER BOOM EXTENSION: 138 IN. (350.5 CM)  
LOWER BOOM ARTICULATION: 0 TO 88°  
UPPER BOOM TRAVEL: 75° TO -25°  
LOWER BOOM INSULATION GAP: 24 IN. (61.0 CM)  
UPPER BOOM INSULATION GAP: 104 IN. (264.2 CM)

## STANDARD EQUIPMENT:

END-MOUNT 24" X 48" X 42" TWO-PERSON PLATFORM  
PLATFORM CAPACITY OF UP TO 700 LB (317.5 KG)  
4-FUNCTION SINGLE STICK  
SAFETY HARNESS WITH ATTACHED LANYARD  
PLATFORM ROTATOR PROVIDES 180 DEGREES OF ROTATION  
CONTINUOUS UNRESTRICTED WORM GEAR ROTATION  
CATEGORY "C" RATING PER ANSI A92.2  
RECTANGULAR, BI-AXIAL EPOXY RESIN, FILAMENT WOUND FIBERGLASS BOOMS  
INDIVIDUAL LEVER LOWER CONTROLS  
TWO SPEED MANUAL THROTTLE CONTROL  
HYDRAULIC PLATFORM LEVELING SYSTEM  
STEEL MAIN BOOM  
FIBERGLASS SECOND SECTION BOOM  
FIBERGLASS LOWER BOOM INSERT  
FULL PRESSURE, OPEN-CENTER HYDRAULIC SYSTEM  
DUAL HYDRAULIC TOOLS WITH FLOW CONTROL  
ENGINE STOP / START  
35 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL80)  
50 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL100 & TL80/112)  
PADDED LOWER BOOM REST  
OUTRIGGER INTERLOCK

**888-925-0858**  
**[www.customtruck.com](http://www.customtruck.com)**

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

