



TEREX TL100
TRANSMISSION AERIAL DEVICE

**IMAGE
COMING
SOON**



SPECS

TL100:

BOTTOM OF PLATFORM: 95.0 FT (29.0 M)
WORKING HEIGHT: 100.0 FT (30.5 M)
HORIZONTAL REACH: 61.9 FT (18.9 M)
BOTTOM OF PLATFORM TO GROUND: -3.14 IN. (-8.0 CM)
UPPER BOOM EXTENSION: 251.7 IN. (639.3 CM)
LOWER BOOM ARTICULATION: 0 TO 88°
UPPER BOOM TRAVEL: 75° TO -25°
LOWER BOOM INSULATION GAP: 24 IN. (61.0 CM)
UPPER BOOM INSULATION GAP: 52 IN. (132.1 CM)

STANDARD EQUIPMENT:

END-MOUNT 24" X 48" X 42" TWO-PERSON PLATFORM
PLATFORM CAPACITY OF UP TO 700 LB (317.5 KG)
4-FUNCTION SINGLE STICK
SAFETY HARNESS WITH ATTACHED LANYARD
PLATFORM ROTATOR PROVIDES 180 DEGREES OF ROTATION
CONTINUOUS UNRESTRICTED WORM GEAR ROTATION
CATEGORY "C" RATING PER ANSI A92.2
RECTANGULAR, BI-AXIAL EPOXY RESIN, FILAMENT WOUND FIBERGLASS BOOMS
INDIVIDUAL LEVER LOWER CONTROLS
TWO SPEED MANUAL THROTTLE CONTROL
HYDRAULIC PLATFORM LEVELING SYSTEM
STEEL MAIN BOOM
FIBERGLASS SECOND SECTION BOOM
FIBERGLASS LOWER BOOM INSERT
FULL PRESSURE, OPEN-CENTER HYDRAULIC SYSTEM
DUAL HYDRAULIC TOOLS WITH FLOW CONTROL
ENGINE STOP / START
35 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL80)
50 GALLON HYDRAULIC OIL RESERVOIR W/ SIGHT & TEMP GAUGE (TL100 & TL80/112)
PADDED LOWER BOOM REST
OUTRIGGER INTERLOCK

888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

