

## **ELLIOTT EQUIPMENT 150F HIREACH**

INSULATED AERIAL WORK PLATFORM, 55' WORKING HEIGHT



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



## **ELLIOTT EQUIPMENT 150F HIREACH**

INSULATED AERIAL WORK PLATFORM, 55' WORKING HEIGHT

## **EQUIPMENT SPECS**

WORKING HEIGHT: 55' / 16,8 M WORKING SIDE REACH: 40' / 12,2 M

**BOOM SECTIONS: 3** 

PLATFORM TYPE: INSULATED TOP-MOUNT PLATFORM CAPACITY: 600 LB / 272 KG PLATFORM SIZE: 40" X 60" / 102 X 152 CM JIB WINCH CAPACITY: 500 LB / 227 KG MAIN WINCH CAPACITY: 3,650 LB / 1656 KG

**OUTRIGGER TYPE FRONT: A-TYPE** 

OUTRIGGER SPREAD FRONT: 12'6" / 3,8 M OUTRIGGER TYPE REAR: A-UNDERSLUNG OUTRIGGER SPREAD REAR: 8' / 2,4 M UNIT WEIGHT (BARE): 11,500 LB / 5216 KG OVERALL HEIGHT: 11'6" / 3,4 M

RECOMMENDED CAB TO AXLE (CA): 120" / 305 CM RECOMMENDED GVWR: 25,999 LB / 11 793 KG







<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.