

TEREX COMMANDER 4042

MOUNTED ON IHI-55 W/LOAD KING TILT TOP TRAILER



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



TEREX COMMANDER 4042

MOUNTED ON IHI-55 W/LOAD KING TILT TOP TRAILER

EQUIPMENT SPECS

GENERAL SPECIFICATIONS:
TEREX C4042 DIGGER DERRICK
UPPER CONTROLS – 24" X 24" X 42" PLATFORM WITH INSULATED LINER
TRANSFERABLE POLE CLAWS
15,000 LB BOOM WINCH TIP
11,250 LB CAPACITY AT 10' RADIUS
COMMAND POST
RADIAL OUTRIGGER MOUNTED ON
BACK OF TRACK MACHINE
12,000 LB TWO SPEED DIGGER WITH 18" ROCK RIPPER AUGER
20,000LB. FRONT HYDRAULIC WINCH

CHASSIS/CARRIER SPECS

KATO IC55
KUBOTA V3800 / 105 HP @ 2400 RPM
TIER 4 FINAL
6.2 MPH (LOW) /7.5 MPH (HIGH)
HST TRANSMISSION SYSTEM
19.5" GROUND CLEARANCE /24" TRACK WIDTH
ROPS CANOPY CAB/ WITH HEAT

4042 TRACK DIGGER

0 LENGTH - 21'8"

LENGTH - 19'5"

WIDTH - 8'2"

HEIGHT - 9'7"

WEIGHT - 26,840 LBS (CLEAN)

TRACK DIGGER & TRAILER

TRAVEL HEIGHT – 12'10"

APPROX. COMBINED WEIGHT – 38,940 LBS







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com