



# TEREX C6060 ON MOROOKA MST-2500VDL TRACK DIGGER DERRICK





# SPECS

C6060 DIGGER DERRICK  
UPPER CONTROLS - 24" X 24" X 42"  
PLATFORM WITH INSULATED LINER  
TRANSFERABLE POLE CLAWS  
15,000 LB TURRET MOUNTED WINCH  
18,100 LB CAPACITY AT 10' RADIUS BARE BOOM  
COMMAND POST  
RADIAL OUTRIGGERS MOUNTED ON TRACK MACHINE  
12,000 LB TWO SPEED DIGGER WITH 24", 30" & 36" ROCK RIPPER AUGERS AVAILABLE SPRING LOADED HYDRAULIC HOSE REEL  
30,000 LB HYDRAULIC WINCH MOUNTED ON THE FRONT OF TRACK MACHINE

MOROOKA MST - 2500VDL  
CATERPILLAR C7.1 / 250 HP  
TIER 4 FINAL EMISSION  
TRAVEL SPEED 0-7.5 MPH  
HST TRANSMISSION SYSTEM WITH  
HST + EMERGENCY BRAKE  
20" GROUND CLEARANCE  
33" TRACK WIDTH / RUBBER TRACKS  
ENCLOSED SINGLE CAB WITH AC/HEAT  
WEIGHT: 50,600 LBS.  
WIDTH: 8'6"  
HEIGHT: 11'10"  
LENGTH: 27'7"  
OVERALL LENGTH: 30'3"

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

