

HOGG & DAVIS OLT38B

OVERHEAD LINE TENSIONER



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



HOGG & DAVIS OLT38B

OVERHEAD LINE TENSIONER

EQUIPMENT SPECS

TENSIONING DEVICE:
MULTI GROOVE BULLWHEELS
RATED AT: 3000 LBS
JACKSTANDS: MANUAL
UNIT LENGTH: 20' 8", WIDTH: 96"
TANDEM LEAF SPRING AXLES
ELECTRIC BRAKES
LED LIGHT PACKAGE
14,000 LBS GAWR
235/85/16 14 PLY TIRES

BULLWHEEL SPECIFICATIONS: DIAMETER (WITH LINING): 38" LINING: (3) URETHANE DIAMETER MOLDED

GROOVE DIAMETER: 1.5"

BRAKING: (2) 1-3/8" THICK DISCS

BRAKE SPECIFICATIONS:

BRAKE MATERIAL: STAINLESS STEEL

DIAMETER: 24"

BRAKING MECHANISM: HYDRAULIC

ACTUATOR: SINGLE SCREW ROTARY ADJUSTMENT

REEL CARRIER SPECIFICATIONS:
REEL CAPACITY: 8,000 LBS.
MAXIMUM REEL WIDTH: 56"
MAXIMUM REEL DIAMETER: 90"
ANTI-OVERSPIN BRAKE: 16" BRONZE

OPTIONAL EQUIPMENT:
MANUAL RETRIEVER FOR REEL
HYDRAULIC REEL RETRIEVER
HYDRAULIC REEL RETRIEVER (TOOL CIRCUIT)
ABS AIR BRAKES
HYDRAULIC OUTRIGGERS (2) REAR
HYDRAULIC TONGUE JACK (1) FRONT
HYDRAULIC OUTRIGGERS COMPLETE (3)
SPARE TIRE & WHEEL
13HP POWER PACK
OPERATOR STATION SEAT







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.