

FELLING FT-16 SLR

SINGLE REEL TRAILER WITH 13,600 LBS CAPACITY



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com



FELLING FT-16 SLR

SINGLE REEL TRAILER WITH 13,600 LBS CAPACITY

EQUIPMENT SPECS

REEL CARRIER SPECIFICATIONS:

CAPACITY: SINGLE 120" D X 70" W X 3" CENTER HOLE X 13,600 LBS 2 7/8" REEL BAR WITH CROSSARM AND (1) LOCKING COLLAR, ROTATING IN BRONZE REEL BAR SADDLE

TENSIONING BRAKE ASSEMBLY:

16" VENTED BRONZE DISC

HYDRAULIC TAKE UP/ PAY OUT ASSEMBLY:

DIRECT CONNECTION TO REEL BAR, ELIMINATES PROBLEMS ASSOCIATED WITH RIM DRIVE SYSTEMS 3,300 FT/LBS TORQUE HYDRAULIC TAKE-UP RETRIEVER 3,700 LBS. OF LINE PULL ON A 24" DRUM @ 3,0TH00 PSI MOTOR SPOOLED W/ REEL BRAKE FOR SMOOTH INSTANT REEL STOPPAGE CONTROL VALVE WITH ADJUSTABLE SPEED CONTROL FOR TAKE UP/ PAY OUT

HYDRAULIC LEVEL WIND (REMOVABLE)

HYDRAULIC POWER PACK: 13 HP GAS ENGINE WITH ELECTRIC START APPROX 6.7 GPM AT 3,600 RPM AND 2250 PSI

TRAILER SPECIFICATIONS:

GVWR: 18,400 LBS., 13,600 LBS. APPROX. PAYLOAD

TANDEM 8,000 LBS. AXLES

ELECTRIC BRAKES

OVERALL LENGTH: 186" WIDTH: 102" HEIGHT: 84.5" WEIGHT: 4,800 LBS

12,000 LBS. SPRING LOADED DROP LEG, SIDE WIND

REAR PIVOTING HYDRAULIC STABILIZER FRAME JACKS

3" ADJUSTABLE LUNETT EYE/PINTLE

12 VOLT WIRING SYSTEM

ICC AND DOT APPROVED LED LIGHTS







^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

888-925-0858 www.customtruck.com